

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Gordon & Gardner, Contract #52 dated Feb. 1855  
 (DCSO records, Volume 9 Page 3661)

-----

Set post, cor. of secs. 1, 6, 7 and 12, from which  
 A Laurel 3" dia. bears S.47°W., 61 lks. dist.  
 A Fir 24" dia. bears N.45°E., 72 lks. dist.  
 A Fir 30" dia. bears N.25°W., 64 lks. dist.  
 A Laurel 3" dia. bears S.23°E., 64 lks. dist.

---

Bureau of Land Management Dependent Resurvey, Norman Price,  
 Under Special Instructions dated April, 1940 - Survey, 1943  
 (DCSO records, Volume 27 Page 11527)

-----

At proportional measurement, set an iron post, 3 ft. long 2"  
 dia. 28" in the ground, with brass cap mdk. T25S

R4W	R3W
S1	S6
S12	S7

1944 from which

A Fir 5" dia. bears N.64°E., 150 lks. dist. marked  
 T 25 S R 3 W S 6 B T.  
 A Fir 5" dia. bears S.6½°W., 93 lks. dist. marked  
 T 25 S R 4 W S 12 B T.  
 Dig pits, 18 x 18 x 12" in each sec., 3 ft.  
 From this point a spring bears S.40°W., 80 lks. flows NE.

---

Doug. Co. Surveyors Office - Vernon Tracy; Mike Darby; Jack  
 Barnett - November 1964 - C.S. File 53/47-53

-----

Found - GLO brass cap in small spring branch & 2 BTs.  
 No trace of 18"x18"x12" pits.  
 5" now 18" D.Fir N.64°E., 99.0 ft. shows good  
 scar. Didn't open.  
 5" now D. Fir S.6½°W., 61.4 ft. shows good  
 scar, Didn't open.  
 New BTs - 15" D.Fir S.55°E., 21.9 ft. mkd: T25S R3W S7 CSBT.  
 5" Cedar N.76°W., 6.1 ft. mkd: S 1 CS BT.  
 Note: Spring is S.40°W., 53.0 ft.

---

Found Ok by Douglas Co. Surveyors Office - Randall W. Smith &  
 Stephen J. Flause - 1/22/1998 - C.S. File 64/79-9

---

Greg Lang - April 2001 - M138-6

-----

Found - 26½" Fir bears N.64°E., 99.0 ft.  
 27½" Fir bears S.6½°W., 61.4 ft.  
 26" Fir bears S.55°E., 21.9 ft. continued next page

