

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 043020

PRIMARY CORNER DESCRIPTION NW Cor. Cruson DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set post NW Corner of Cl. 43, from which
A B.Oak 8" dia. bears N.75°W., 25 lks.
A B.Oak 15" dia. bears S.80°E., 52 lks.

H.L. Eppstein, N.E. Richardson; B.A. Lane; Milton Palm;
D.L. Byers; J.H. Byers - 1934 - "Old" Cor. renewal Vol. 1
Page 54 (No other source record found, 8/1991 V.L.)

Found old stake badly rotted, found old scribe marks.
Measures out correctly for distance from Sec. Cor. Could not
find old BTs. Set 4" x 4" x 24" Cedar post mkd. on it N.W.
Cor. Cl. 43. Marked:
Oak 10" dia. bears S.34½°W., 13 ft.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; M. Stone
M. Darby - May, 1964 - C.S. File 49/124-87

Found - Old cedar stake lying on ground at corner.
16" W.Oak S.34½°W., 13.0 ft. shows very good scars,
didn't open.
Dead B.Oak stump 10 to 12 ft. high, N.75°W., 16.5
ft., center rotted away, Orig. BT.
No trace of orig. SE bearing tree.
Brass cap for Sec. cor. to Secs. 1, 2, 11 and 12
bears South, 37.6 ft.
Set - Brass cap at cor. mkd. County Surveyors Office 1964
T25S R5W N.W. DLC 43
New BT - 11" D.Fir N.24½°E., 21.3 ft. mkd. NW DLC 43 CS BT.
Fence corner, fences North & East, bears S.31°W., 30.0 ft.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - July 29, 1997 - C.S. 64/71-25

Mon. Fd.- 2½" dia. Brass cap on a 1½" O.D. iron pipe,
protrudes 6" above ground. (1964)
Bt's Fd.- 8" now down and rotted Oak remains found near rec.
"N75°W., 16.5'" OBT.
10" now down and rotted Oak no scribing visible root
hole, bears S.34½°W., 13' (agrees with rec.)
1934.
11" now 14" dia. 1' high rotted D.Fir stump,
illegible scribing found, bears N.24½°E.,
21.3' (agrees with rec.) 1964

Cont. next page

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 043020

PRIMARY CORNER DESCRIPTION NW Cor. Cruson DLC #43

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories -

15" D.Fir, double blazed and scribed "NW DLC 43 CS BT", bears N.21°E., 34.6'.

13" dia. W.Oak, double blazed and scribed "NW DLC 43 CS BT", bears S.62½°W., 11.7'.

DCSO BC/IP SW COR SEC 1, bears south 36.7' (rec. south 37.6').

19" Madrone, with SW facing blaze scribed "T25S R5W S1 CS BT", bears N.77°E., 34.7'.

Fd. ok by Carl Sweeden - 9/1998 - M 130-37

Fd. OK by Carl Sweeden - May 2001 - LP 2001-0053