

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 058030

PRIMARY CORNER DESCRIPTION SW Cor. Reed DLC #58

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

To SW cor. Cl. 58, from which
A B.Oak 10" dia. bears S.83°W., 11 lks.
Raised mound with trench as per instructions.

F.C. Frear, Deputy Co. Surveyor - Wit. R.L. Stearns; Bob Davis
Feb-March 1919 - R.M. 1-4, C.S. File 2/17; F.B. 46 Pg 14

Set a 3/4" x 30" Iron pipe & 4" x 36" cedar stake. From which
A 10" Fir S.73¼°E., 21 lks.
A 12" Fir S.22°E., 19 lks.

Douglas Co. Surveyors Office - Milo Godfrey - May. 1964 - C.S.
File 49/124-82

Fd. ½" iron pipe approx. 5 ft. NW of 3-way fence corner. No
trace of any BTs found.
NOTE: This corner is considered as being looked for and
not found. 8/21/96 DCS0, JC

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - June, 18, 1997 - C.S. 64/75-10

Mon. FD.- 1" inside dia. iron pipe flush with ground (1919)
Note: Recorded as 3/4" I.P. in 1919
Note: Renewal in 1964 denotes a ½" I.P. near a
fence corner. No fence corner or ½" I.P.
found in this area I believe this renewal's
corner I.D. to be in error.
Bt's Fd.- 10" now scattered rotted oak remains found near
record "S83°W., 7.3'. OBT ?
12" now 12" dia. 2' high badly rotted D.Fir stump,
scribing found "CSC 58 Bt", bears S.22°E.,
12.5' (agrees with rec.) 1919.
10" now badly rotted D.Fir stump of indeterminable
size scribing found "CSC 58 BT", bears
S.73¼°E., 13.9' (agrees with rec.) 1919.

(Cont. Next Page)

TOWNSHIP 25 RANGE northerly POINT IDENTIFIER # 058030

PRIMARY CORNER DESCRIPTION SW Cor. Reed DLC #58

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Bt's- 9" dia. D.Fir, double blazed and scribed "SW DLC 58
CS Bt", bears S.85½°W., 29'.
4" dia. Pistol butt maple, double blazed and scribed
"X BT", bears N.67½°E., 8.8' to center of root
crown.
11" dia. D.Fir double blazed and scribed "SW DLC 59
CS BT", bears N.80½°E., 52.6'.
24" dia. D.Fir, double blazed and scribed "SW DLC 58
CS BT", bears N.68°W., 14.8' to center of
trunk.
Corner lies on a steep northerly slope