

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 058040

PRIMARY CORNER DESCRIPTION Int. SW Cor. Reed DLC #58

Alias <u>300553</u>	Description <u>Point of E. Bdy Sec 8</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #28 dated April 1854

Set Post, from which

A B.Oak 10" dia. bears N.10°E., 10 lks.

A B.Oak 13" dia. bears S.10°E., 150 lks.

F.C. Frear, Deputy Co. Surveyor - R.L. Stearns; Bob Davis,
wit. - For: Stearns Estates - R.M. 1-4 - C.S. 2/17 and
Field Book 46 Page 26 - Feb.-March, 1919

Set a ¾" x 40" galv. I.P. & 4" x 36" Fir stake, from which

A 6" Fir bears S.46°W., 27½ lks.

A 30" B.Oak bears N.4¾°E., 46½ lks.

A.R. Evans, D.C.S. - R.L. Matthews Witness - April, 1950
C.S. File 47/32

Found ½" I.P. (¾" outside meas) set by Frear in 1917 - checks
fairly well for distance & bearing from Sec. Cor. 5,4,8,9 &
for dist. & bearing from Ext. L Cor same claim. BTs gone.
Blazed & scribed new BT:

A 6" Laurel S.48°E., 7.8 ft. mkd. S Int "L" Cor, Cl. 58
C.S.B.T.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; M.Stone;
M. Darby - May 1964 - C.S. File 49/124-83

Found - ½" Iron pipe at corner.

8" Laurel S.48°E., 7.8 ft. bark scribed

Stump hole N.4¾°E., 31.0 ft. No trace of other BT.

New BT - 5" D.Fir N.54½°E., 15.5 ft. mkd. DLC 58 CS BT.

Rescribed - 8" Madrone S.48°E., 7.8 ft. mkd. DLC 58 CS BT.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - June 26, 97 - C.S. 64/75-17

Mon. Fd.- ½" I.D. iron pipe protrudes 3" above ground. (1919)
¾" I.D. i.p. the SSW cor of DLC 58 bears S.12½°E.,
79.3'.

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 058040

PRIMARY CORNER DESCRIPTION Int. SW Cor. Reed DLC #58

Alias 300553 Description Point of E. Bdy Sec. 8

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Accessories Fd. -

30" B.Oak now root hole near rec. "N.4 3/4°E.,
30.7'.

6" now 10" dia. Madrone, with a fully healed double
blaze, bears S.48°E., 7.8' (agrees with rec.)
1950

5" now 20" dia. D.Fir, with a fully healed blaze,
bears N.54½°E., 15.5' (agrees with rec.) 1964

New Accessories -

12" dia. D.Fir, double blazed and scribed "INT SW
DLC 58 CS BT", bears S.24°W., 26.7'.

9" dia. Madrone, double blazed and scribed "INT SW
DLC 58 CS BT", bears N.16½°W., 11.2'.

Fd. IP & 4 BTs by K. Hoffine - 3/2011 - M162-25