

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 058050

PRIMARY CORNER DESCRIPTION SSW Cor. Reed DLC #58

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1854

-----  
Set post, from which

A B.Oak 13" dia. bears S.15°E., 31 lks.

A B.Oak 10" dia. bears N.5°E., 127 lks.

-----  
F.C. Frear, Deputy Co. Surveyor - R.L. Stearns; Bob Davis,  
Witnesses - For: Stearns Estates - R.M. 1-4; C.S. File 2/17;  
Field Book 46 Pg. 26 - Feb, March, 1919

-----  
Set a 1" x 40" Iron pipe from which

A 10" W.Oak bears N.75¾°E., 12 lks.

A 6" Fir bears S.41½°W., 1½ lks.

-----  
A.R. Evans, D.C.S. - R.L. Matthews, Wit. - April 1950  
C.S. File 47/32

-----  
Found ¾" I.P. (1" outside meas) set by Frear in 1917., checks  
for bearing & distance from Int. "L" Cor. same Claim set at  
same time by Frear. BTs gone. Blazed & Scribed:

A 4" Laurel, N.54°E., 36.4 ft. mkd. Ext. "L" Cor. Cl. 58  
C.S.B.T.

-----  
Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; M. Stone  
M. Darby - May 1964 - C.S. File 49/124-84

-----  
Found - ¾" Iron pipe at corner.

6" Laurel N.54°E., 36.4 ft. (bark scribed)

No other BTs found - Cor. is 3 ft. S.W. of fence  
corner.

New BTs - 8" Madrone N.37°W., 29.0 ft. mkd. DLC 58 CS BT.

10" Madrone S.31°E., 21.9 ft. mkd. DLC 58 CS BT.

-----  
Douglas County Surveyors Office - Randall Smith & Stephen  
Flause - June 26, 1997 - C.S. 64/75-16

-----  
Mon. Fd.- 3/4" I.D. iron pipe protrudes 7" above ground.  
(1919)

½" I.D. i.p. the Int. SW cor. of DLC 58, bears  
N.12½°W., 19.3'.

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 058050

PRIMARY CORNER DESCRIPTION SSW Cor. Reed DLC #58

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Accessories Fd. -  
4" now 9" dia. Madrone, no bark scribing visible, bears N.52°E., 36.4' (rec. N.54°E., 36.4') 1956 rebark scribe "SSW DLC 58 CS BT".  
8" now 10" dia. Madrone, with a partially healed double blaze scribing visible "BT", bears N.37°W., 29.1' to root crown of scribed trunk, 1964  
10" now multi trunked madrone, with a fully healed single blaze on SW'ly 16" dia. trunk root crown, bears S.31°E., 21.9' (agrees with rec.) 1964  
New Accessories -  
14" dia. D.Fir, double blazed and scribed "SSW DLC 58 CS BT", bears N.53°W., 30.1'.  
Corner lies west 12' from a easterly and northerly running fence lines.

Fd. IP & 4 BTs by K. Hoffine - 3/2011 - M162-25