

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. 18 & 19; 13 & 24 of T25-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----

Set post cor. to Secs. 13, 18, 19, and 24, from which  
An Ash 10" dia. bears N.83½°W., 326 lks.  
An Ash 8" dia. bears S.47°W., 297 lks.  
Made trench, no other trees near.

Francis L. Ingram, Douglas Co. Surveyor - John Powell & Crew  
May 1972 - C.S. File 56/16 and M42-61  
-----

This corner set from survey of Range line.

Set brass cap at cor. mkd. County Surveyor's R T 25 S R  
Office 6 S 13 S 18 5  
1972 W S 24 S 19 W

New BTs - 18" W.Oak N.75°W. 48.4 ft. scribed T25S R6W S13 CSBT  
Bearing Objects:

5/8" Iron Rod North 10.0 ft.  
5/8" Iron Rod South 10.0 ft.  
5/8" Iron Rod East 10.0 ft.

Also set a steel fence post with survey mark sign alongside  
Brass Cap.

Fd. BC, bearing tree & objects - Glen Baughman - April 1993 -  
Vol. 1 Pg. 1 A & B

Fd. BC & 1 BT by D. Bentz, Sept. 1993 (Filed 12/94) - 1994-108  
Fd. OK, Oct. 1995 by Bentz - M123-20  
Fd. OK, Oct. 1997 by Bentz - 1997-0133  
-----

Found Ok by Douglas Co. Surveyors Office - Randall W. Smith  
& Stephen J. Flause - 10/9/1997 - C.S. File 64/79-9  
Fd. Ok by Bentz - 11/1998 - M 130-71  
-----

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 3/29/1999 - C.S. File 66/8-30 & M131-50  
-----

Found: 2½" brass cap on a 1½" o.d. iron pipe, protrudes  
6" above ground. 1972

18" now 25" w. oak with a fully healed double  
blaze, bears N.52½°W., 67.8 ft.

East 5/8" BO from 1972, bears N.6°E., 28.6 ft.

New: 1972 brass cap is sawn off & a yellow DCSO plastic  
cap set in iron pipe center, protrudes 3"  
above ground. continued next page

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec Cor 18 & 19; 13 & 24 of T25-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set - 2 3/8" brass cap on a 1 3/8" o.d. by 32" long iron pipe is set at new proportioned position, protrudes 7" above ground.  
5" dia. D.Fir double blazed and scribed "X BT" bears N.36½°W., 80.5 ft.  
1½" o.d. iron pipe, 1972, bears N.13 3/4°W. 29.59 ft.  
Added 3/18/2021 -  
This position was re-proportioned - See M131-50  
Also found (1999) the 3 IRs that were set in 1972 and were 10 ft N, S & E. Of the previous corner location - See sketch in file.

March 15, 2000 - DCSO  
-----  
Note - i.e. engineering will reference out this location - the existing monument will be buried.