

PRIMARY CORNER DESCRIPTION Sec Cor for 6 & 7; 1 & 12, T25-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853  
-----  
Set post cor. to Secs. 1, 6, 7 and 12.  
Deposited 2 quarts charred wood and raised mound  
with trench and pits.

Francis L. Ingram, Douglas Co. Surveyor - John Powell & Crew  
May 1972 - C.S. file 56/16 and M 42-61  
-----  
This corner set from survey of Range line.  
Set brass cap at cor. mkd. County Surveyor's R T 25 S R  
Office 6 S 1 | S 6 5  
1972 W S 12 | S 7 W  
New BTs - 15" D.Fir N.26°E., 300.7 ft. scribed T25S R5W  
S 6 CS BT.  
16" W.Oak N.87°E., 180.0 ft. scribed T25S R5W  
S 6 CS BT.

Douglas Co. Surveyor's Office; Randall Smith, Stephen Flause,  
May, 1997 - C.S. File 64/79-9  
-----  
Found OK.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 3/30/1999 - C.S. File 66/8-34 & M131-50  
-----  
Found: 2½" brass cap on a 1½" o.d. iron pipe  
protrudes 9" above ground. 1972  
Bearings & distances taken from new corner position  
15" now 35" dia. d. fir with a fully healed  
blaze, bears N.25°E., 336.3 ft. (1972 northerly  
BT.) note distance to this BT. from 1972  
BC/IP is 330.7 ft. not 300.7 ft. as per rec.  
16" now 22" dia. w. oak with a fully healed blaze,  
bears N.85°E., 179.2 ft. (1972 easterly BT.)  
Set: 1972 brass cap sawn off and a DCSO yellow plastic  
cap is set in it's center, now protrudes 7"  
above ground.  
2 3/8" dia. brass cap on a 1 3/8" o.d. by 32" long  
iron pipe, is set at NEW PROPORTIONED POSITION.  
Protrudes 6" above ground.

continued next page

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Cor. Secs. 6 & 7; 1 & 12 T25-6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

DOUGLAS COUNTY SURVEYORS  
T25S  
R    S1 | S6    R  
6    S12 | S7    5  
W    1999    W  
OFFICE  
1½" o.d. iron pipe, bears N.10 3/4°W., 6.5 FT  
This position was re-proportioned - See M131-50

Fd. Ok by C. Sweeden, 5/2006 - 2007-0130  
Fd. Ok by C. Sweeden, 4/2008 - 2008-0064