TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; and 6 of T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set qr. sec. post, from which:
drove chained stake and raised mound with trench.

Francis L. Ingram, Deputy Co. Surveyor - John M. Powell
January 21, 1972 - C.S. File 56/10 and M 44-48

This corner set from resurvey of township line
Set - Brass cap at ¼ cor. mkd. County Surveyors Office
1972 T 25 S R 5 W
¼ S 31
S 6
T 26 S

Bearing Objects:
5/8" Iron rod S.43°W., 17.0 ft.
5/8" Iron rod S.31°E., 14.4 ft. (SE I.R. set at fence cor. Fences running E-W-S)
This cor. lies 12.0 ft. north of East-West fence line.

Found brass cap, April,1988, D. Bentz - M 106-4

Fd BC by Mark Heimburger, 9/2006 - M146-47

Grid	N:	624,504.223
Grid	E:	4,166,992.268
Latitude		43°20'42.706"
Longitude		-123°20'10.330"
Convergence		-1°56'25.37"

Andrew Ausland, ODOT - June 2012 - M163-64 A-C

Fd. 2½" dia., brass disk (properly) stamped 0.1 ft. above surface, good condition.

Fd. DCSO BC by M Heimburger, 3/2014 - M168-9