TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
A Y.Oak 28" dia. bears S.88½°W., 115 lks. dist.
A W.Oak 12" dia. bears N.51°W., 119 lks. dist.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey, Clete Putnam - May 1960 - C.S. file 49/124-60

Found - I believe we have found both orig. BTs. No scribing found on either BT. Orig. 12" now 22" W.Oak N.51°W., 78.5 ft. opened about 40 years ago, old face rotted.
Orig. SW BT, now down & badly rotted, checks record bearing & distance.

New BTs - 10" R.Fir bears N.63°E., 41.0 ft. scribed ¼ S30 CSBT
7" R.Fir bears S.40°W., 8.0 ft. scribed ¼ S31 CS BT.

Set brass cap at cor. mkd. County Surveyor's Office 1960 ¼ S30 / S31 T25S R5W

(Sketch in CS File showing relationship of cor. to fences._

Found OK, Donald Bentz, Sept. 1986 - M 102-48
Found OK, Daniel Baker, Oct. 1995 - M 119-75
Fd. BCIP & accessories per rec. R Badgley 10/2021 2021-0047B