TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32; 5 & 6, T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post, cor. to secs. 31, 32, 5 & 5, from which
An Ash, 10" dia. bears S.5°E., 192 lks. dist.
An Ash 8" dia. bears S.69°W., 256 lks. dist.
An Ash 7" dia. bears N.23½°E., 326 lks. dist.
An Ash 8" dia. bears N.74°W., 217 lks. dist.

Francis L. Ingram, Deputy Co. Surveyor; John M. Powell
January 21, 1972 - C.S. File 56/10 and M 44-48

This corner set from resurvey of township line.
Set - Brass cap at sec. cor. mkd. County Surveyors Office 1972 T 25 S R 5 W

S 31	S 32
S 6	S 5

T 26 S

New BTs - 30" W.Oak N.36°E., 78.6 ft. scribed T25S R5W S32 CS BT.
13" W.Oak N.33½°W., 97.0 ft. scribed T25S R5W S31 CS BT.
13" W.Oak S.30°E., 117.7 ft. scribed T26S R5W S5 CS BT.
12" Ash S.83°W., 133.7 ft. scribed T26S R5W S6 CSBT
This cor. lies between 2 creeks, east 300 ft., west 130 ft.

Found OK, H. Pieske, May 1987 - M 104-20
Fd. OK - Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - July 1997 - C.S. File 64/79-9

Fd BC by Mark Heimburger, 9/2006 - M146-47

Grid	N: 624,409.287
Grid	E: 4,169,633.646
Latitude	43°20'42.651"
Longitude	-123°19'34.558"
Convergence	-1°56'00.90"

Fd. BC by M. Schulze, 11/2012 - M164-47
Fd. BCIP & accessories per rec. R Badgley 10/2021 2021-0047B