

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor. Secs 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Robert Elder & Henry Gile, Deputy Surveyors under Contract #31 dated April, 1853 (DCSO records Vol. 9 page 3795  
-----  
Set post cor. to secs. 29, 30, 31, & 32, from which  
An Ash, 12" dia., bears S.½°W., 298 lks.  
A W.Oak, 18" dia., bears S.27¾°E., 234 lks.  
A W.Oak, 24" dia., bears N.25¼°E., 242 lks.  
An Ash, 18" dia., bears N.16°W., 242 lks.  
Land all level prairie excepting along creek, which is skirted with oak and ash timber.

Russell Badgley - For: Jon Martz - 10/2021 - 2021-0047B  
-----  
Set by double proportion -  
A 1"x30" iron pipe with a 2½" brass cap marked;  
T25S R5W  
S30|S29  
S31|S32  
2021  
PLS 70716  
  
From which -  
A 15" Alder bears N.83°00'W., 241.4' bark scribed "T25S R5W S30 BT" w/washer "PLS70716"  
A 14" Oak bears N.26°30'E., 129.2' scribed in double blaze "T25S R5W S29 BT" w/washer "PLS70716"  
A 10" Oak bears S.59°15'E., 100.5' scribed in double blaze "T25S R5W S32 BT" w/washer "PLS70716"  
A 5/8"X30" iron rod bears S.39°12'48"W., 74.58' with a 2" alum. cap marked "RM"