

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Robert Elder & Henry Gile, Deputy Surveyors under Contract #31 dated April, 1853 (DCSO records Vol. 9 page 3796

-----  
Set post cor. to secs. 19, 20, 29, & 30  
Deposited a rock 12x7x5 and raised mound with trench as per instructions.

Russell Badgley - For: Jon Martz - 10/2021 - 2021-0047B

-----  
Set by double proportion -  
A 1"x30" iron pipe with a 2½" brass cap marked;  
T25S R5W  
S19|S20  
S30|S29  
2021  
PLS 70716

From which -  
A 5/8"X30" iron rod bears S.37°17'22"W., 62.90' with a 2" alum. cap marked "RM"  
A PACIFICORP Power Pole (#199001) with a mag nail in the side bears N.66°45'W 242.8'  
A PACIFICORP Power Pole (#200000) with a mag nail in the side bears N.29°30'E., 33.5'  
A 11" Alder bears S.4°15'W., 90.1' bark scribed "T25S R5W S29 BT" w/washer "PLS70716"