TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; and S.5 of T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set qr. sec. post, from which
An Ash 12" dia. bears S.65°E., 359 lks. dist.
A W.Oak 24" dia. bears N.52°E., 408 lks. dist.

Francis L. Ingram, Deputy Co. Surveyor - John M. Powell
January 21, 1972 - C.S. File 56/10 and M 44-48

This corner set from resurvey of township line for T26-5 and T25-5

Set - Brass cap at ¼ cor. mkd. County Surveyors T25S R5W
(Steel fence post alongside) Office S 32
1972 S 5

New BTs - 12" W.Oak N.54°E., 179.6 ft. scribed ¼ S32 CS BT.
22" Triple Ash S.10°W., 229.8 ft. scribed ¼ S5 CSBT

East-West fence bears South 18.0 ft.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - July 14, 1997 - C.S. 64/71-23

Mon. Fd.- 2½" dia. brass cap on an iron pipe, flush with ground (1972)

Bt's Fd.- 12" now 18" dia. W.Oak, with a fully healed double blaze, bears N.54°E., 179.6' (agrees with rec.) 1972.
1972 SW Ash BT now gone

New Accessories -
16" dia. Ash, double blazed and scribed "¼ S5 CS BT", bears S.75½°E., 280.7'.
5/8" by 30" iron rod with alum. cap stamped "B01 1997" protrudes 6" above ground in E-W fence line, bears S.14°W., 18.9'.
5/8" by 30" iron rod with alum. cap stamped "B02 1997" protrudes 6" above ground in N-S fence line, bears N.84°W., 68.2'.

Corner lies 18' north of a E-W fence line

DCSO-GIS Corner visitation - 8/17/2004 - Typed: 1/24/2011 - C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK

Fd. BC by M. Schulze, 11/2012 - M164-47