

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33; 5 & 4 of T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post, cor. to secs. 32, 33, 4 & 5, from which
A W.Oak 14" dia. bears S.6¼°E., 67 lks. dist.
A W.Oak 18" dia. bears S.58 3/4°W., 66 lks. dist.
A Pine, 36" dia. bears N.17°W., 134 lks. dist.
A Y.Oak 10" dia. bears N.17 3/4°E., 61 lks. dist.

Francis L. Ingram, Deputy Co. Surveyor; John M. Powell
January 21, 1972 - C.S. File 56/10 and M 44-48

This corner set from resurvey of township line for T26-5 and
T25-5.

Set - Brass cap at Sec. cor. mkd. County Surveyors Office
1972 T 25 S R 5 W
S 32 | S 33
S 5 | S 4

New BTs - 10" W.Oak N.31½°W., 37.0 ft. scribed T25S R5W
S32 CS BT.
12" W.Oak N.3°E., 37.3 ft. scribed T25S R5W S33 CSBT
12" W.Oak S.25°E., 15.2 ft. scribed T26S R5W S4 CSBT
10" W.Oak S.28°W., 40.6 ft. scribed T26S R5W S5 CSBT
Fence corner bears S.40°E., 21.6 ft.

Daniel Baker - for: Waggoner - 10/05/95 - M 119-74

Mon. Fd.- Douglas Co. Brass cap dated 1972
Bt's Fd.- 18" oak, N.4°E. 37.5', to set spike - closed face
18" oak, S.20°E. 14.9', to set spike - closed face
16" ash, S.29°W. 40', to set spike - scribe visible
20" oak, N.36°W. 36.6', to set spike - closed face
Set - 6' metal fence post 1' north

DCSO-GIS Corner visitation - 8/17/2004 - Typed: 1/24/2011 -
C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK

Fd. BC by M. Schulze, 11/2012 - M164-47