

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to Secs. 8, 9, 16 and 17, from which  
A Y.oak 12" dia. bears S.32½°E., 105 lks.  
A Y.oak 14" dia. bears N.69°W., 36 lks.  
A Y.oak 14" dia. bears N.57½°E., 100 lks.  
A Y.oak 24" dia. bears S.38½°W., 40 lks.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey, Clete Putnam - May 4, 1960 - C.S. File 49/124-52

-----  
Found - Orig. 24" now 30" rotted Oak, down & out of position, about 8 ft. downhill. I find good reverse scribing "R5WTBT".  
Stump hole & remnants of Oak N.69°W., 23.8 ft., old & rotted stump, that shows old axe marks and checks record dist. & bearing for Orig. NE BT. No scribing found.

Set brass cap at cor. mkd. County Surveyor's S 8 | S 9 T25S R5W  
Office, 1960 S17LS16

New BTs - 11" R.Fir bears S.77°E., 32.6 ft. scribed S16 T25S R5W CS BT.  
11" R.Fir bears N.6½°E., 59.8 ft. scribed S9 T25S R5W CS BT.  
5" R.Fir bears N.71½°W., 52.8 ft. scribed S8 CSBT.  
16" R.Fir bears S.42°W., 116.7 ft. scribed S17 T25S R5W CS BT.

Found and used, BLM dependent Resurvey, 1962 - DCS0 records Volume 31, Page 13151-52

Douglas County Surveyors Office - Randall Smith & Stephen Flaese - June 4, 1996 - C.S. 64/74-6

-----  
Mon. Fd.- 2½" dia. brass cap on a 1½" O.D. iron pipe, protrudes 17" above ground. (1960).

Accessories Fd. -

11" now 23" dia. 1½' high D.Fir Stump, with a healed lower blaze, bears N.4°E., 59.8' (rec. N.6½°E., 59.8') 1960.

16" now 24" dia. 1½' high D.Fir stump, with a healed lower blaze, bears S.40°W., 116.7' (rec. S.42°W., 116.7') 1960 opened blaze found scribing "B".

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

11" now 20" dia. D.Fir, with a fully healed double blaze, bears S.77°E., 32.6' (agrees with rec.) 1960.  
NW BT from 1960 now gone.  
No evidence of Orig. BT's found.

New Accessories -

10" dia. D.Fir, double blazed and scribed "T25S R5W S9 CS BT", bears N.70½°E., 16.8'.  
12" dia. Madrone, bark scribed "T25S R5W S16 CS BT", bears S.27°E., 12.9'.  
6" dia. D.Fir, double blazed and scribed "T25S R5W S8 CS BT", bear N.34°W., 4.9'.