

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 33; & 4 of T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ sec. post, from which
A Fir, 15" dia. bears N.5½°W., 64 lks. dist.
A Dogwood 8" dia. bears S.15°W., 66 lks. dist.

Francis L. Ingram, Deputy Co. Surveyor - John M. Powell -
January 21, 1972 - C.S. File 56/10 and M 44-48

This corner set from resurvey of township line for T25-5
and T26-5

Set - Brass cap at ¼ cor. mkd. County Surveyors Office
1972 T 25 S R 5 W

¼ S 33
S 4

T 26 S

New BTs- 15" D.Fir S.70°E., 18.3 ft. scribed ¼ S4 CS BT.
15" Maple N.11°W., 19.6 ft. scribed ¼ S33 CS BT.

Daniel Baker - for: Waggoner - 10/05/95 - M 119-74

Set - 1" x 36" Iron pipe with brass cap dated 1994
New - 8" alder, N.86½°W., 34.6' to spike scribed "¼ S33 BT"
9" ash, N.13°E., 89.5' to spike scribed "¼ S33 BT"
10" alder, S.66°E., 82.7' to spike scribe "¼ S4 BT"
7" fir, S.71°W., 100.6' to spike scribed "¼ S4 BT"
6' aluminum fence post 1' east

Note- Brass cap for ¼ corner dated 1972, per M44-48, bears
S.7°47'11"W, 152.27' cap removed 10/13/94 per Do.
Co. request.

Carl Sweeden - For: Tim Clark - Sept. 2016 - M172-33 A&B

Found - 1" I.Pipe with 1994 brass cap
8" now 19" alder BT, N.86½°W., 34.6', scar, tag,
nail in bole.
9" now 14" Ash BT, N.13°E., 89.5', double blazed,
scribe vis., tag, nail in bole
10" Alder BT, S.66°E., 82.7', now dead and down, tag
7" now 27" Fir BT, S.71°W., 100.6', double scars,
tag, alum. Post 1.0 E.