

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder and Gile Under Contract #31 dated April 7, 1853 (DCSO records, Volume 9 Page 3791)

-----  
Set 1/4 sec. post, from which  
    A W.Oak 12" dia., bears S.17°W., 263 lks. dist.  
    An Ash, 5" dia., bears N.37½°W., 519 lks. dist.

-----  
Robert L. Dolan, L.S. 1076 - For: Edward & Lucille Koch  
May 1992 - M 115-28

-----  
Set - 5/8" x 30" Iron rod with cap mkd. LS 1076.  
(The 1/4 Corner was computed by tying the section corner common to sections 15, 16, 21 and 22, then using the bearing N.89°31'00"W., from the GLO plat a distance of 2638.68 ft. as per GLO plat. This corner IS NOT necessarily the true 1/4 corner.)

-----  
Douglas County Surveyors Office - Randall Smith & Stephen  
Flause - June 30, 1997 - C.S. 64/75-27

-----  
Orig. Bt's not found