

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3793)

Set 1/4 Sec. post, from which
 A Laurel 36" dia. bears S.15°W., 24 lks. dist.
 A Y.Oak 6" dia. bears N.21½°E., 10 lks. dist.

BLM dependent Resurvey, Patrick J. Reynolds, under Group #
476 - Survey July 25-August 30, 1962 (DCSO records Volume
31 Page 13154)

The 1/4 sec. cor. of secs. 4 & 9, monumented with an iron bolt
set in a concrete post, 6" dia. projecting 6" above ground
from which the only remaining orig. bearing tree:

 An Oak snag 17" dia. bears N.21½°E., 10 lks. dist. with
 no marks remaining on decayed blaze.

and a bearing tree of which I have no record:

 An Oak 23" dia. bears N.41°E., 31 lks. dist. with scribe
 marks 1/4 S visible on partially healed blaze.

At the corner point:

Set an I.P. 30" long 2½" dia. 28" in the ground, with brass
cap marked:

 T 25 S R 5 W

 1/4 S 4

 S 9

 1962

 from which:

 An Oak 8" dia. bears S.17°W., 21 lks. dist. marked

 1/4 S 9 BT.

 Deposit the concrete post alongside the iron post.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - June 26, 1997 - C.S. 64/75-14

Mon. Fd.- 3¼" brass cap on a 2½" O.D. iron pipe protrudes 1"
above ground. 1962.

 6" dia. concrete post with 3/4" square bolt head is
 found along north edge of Bc/IP.

Accessories Fd.-

 6" now 17" dia. Oak snag, with a previously opened
 unhealed blaze, no scribing visible, bears
 N.21½°E., 8.1' (rec. N.21½°E., 6.6') OBT.

 23" Oak now 24" dia. B.Oak (noted as not of record
 by 1962 BLM) has a partially healed previously
 opened blaze, no scribing visible, bears
 N.41°E., 20.5' (agrees with rec.)

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

8" now 9" dia. W.Oak, with a fully healed single blaze, bears S.17°W., 13.9' (agrees with rec.)
1962
New Accessories -
6" Maple, double blazed and scribed "¼ S4 CS BT", bears N.75°E., 8.7'.
5" D.Fir, double blazed and scribed "¼ S4 CS BT", bears N.83°W., 16.5'.

Fd. by Carl Sweeden, 7/1999 M131-80