

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 21, 22, 27 & 28, from which
A Y.Oak 14" dia. bears S.21°W., 18 lks. dist.
A Laurel 18" dia. bears S.78°E., 83 lks. dist.
A Laurel 8" dia. bears N.88½°E., 86 lks. dist.
A Fir 18" dia. bears N.20°W., 153 lks. dist.

J.W. Cole, C.S.; N.E. Richardson; Mr. Breager - August 1923
For: Balfour & Guthrie - Vol. 3 Pg. 82 - C.S. File 2/12

From stump of original Laurel S.75½°E., 83 lks. and 36" Fir
N.20°W., 156 lks. Fir shows peculiar but no scribe mks.
Chopped tree open but no mks. show. No marks visible on
either.

Set a rock 10" x 10" x 20" marked X C.S., three notches on
East side & two notches on South side.

Marked new trees:

A Fir 14" S.66°E., 15.4 ft.
A Fir 8" N.48°15'E., 10.2 ft.
A rock 3 ft. high N.45°W., 19.7 ft.

Follet & Ford - For: Cottage Grove Lbr. Co. - April, 1955
M 28-41 and C.S. 41/376

Set Hub & Tack in old fence corner.
Hole from original County BTs.
Found rock 3.0 ft. high x 4.0 x 3.0 & a 14" Fir S.66°E. 15.4'.

Bruce Rogers For: Fred Harrington - August, 1972 - C.S. 55/289

Set point from Fir BT S.66°E., 15.4 ft.

Doug. Co. Surveyors - J.Heritage; G.E. Commins - Jan. 1973
C.S. File 56/25-1

Found - Nail in log set by Bryon(?) & B. Rogers from orig.
BT.

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - 5/8" I.Rod, N.37°W., 5.14 ft.
 5/8" I.Rod, N.46°E., 7.75 ft.
 5/8" I.Rod, S.11°W., 5.80 ft.
 5/8" I.Rod, S.64°E., 7.23 ft.

Douglas Co. Surveyors Office - Randall Smith & Stephen
Flause - July 23, 1997 - C.S. 64/75-32

Mon. Fd.- No corner monument found
Bt's Fd.-14" now 24" dia.4' high rotted D.fir snag shows
 evidence of old search for scribing. None
 visible or found, bears S.66°E., 15.4'
 (agree with rec.) 1923?

5/8" I.R. from 1973 DCSO renewal are found
N.37°W., 5.14'
N.46°E., 7.75'
S.11°W., 5.80
S.64°E., 7.23

(All agree with record)

Mon. Set- at a position determined from 1973 DCSO 5/8"
I.R.'s

 and snag a 2 3/8" brass cap on a 1 3/8" O.D.
 iron pipe is set, protrudes 6" above ground.

New Accessories -

17" D.fir double blazed and scribed "T25S R5W S21
CS BT, bears N.27½°W., 10.6'.

5" D.fir double blazed and scribed "X BT", bears
N.78°E., 23.8'.

18" Madrone double blazed and scribed "T25s R5W
S27 CS BT", bears S.62½°W., 31.8'.

Corner lies near the intersection of a E-W-S running down
fence line (old).

Old clear cuts NE & SW new clear cut NW old growth SE.

Found OK by K. Hoffine, Dec, 2001 - M137-29