TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set ¼ Sec. post, from which
A Laurel 10" dia. bears N.58½°W., 22 lks. dist.
A Laurel 8" dia. bears N.81½°E., 59 lks. dist.

Bruce Rogers, for: Fred Harrington - August 1972
C.S. File 55/289

Set 5/8" Iron Rod.

Douglas County Surveyors Office - Cooper Creek Survey
John Powell; J. Heritage; G. Commins - Feb. 1973
C.S. File 56/28 and R.M. 2-38

Found - 5/8" I.R. single proportioned by B. Rogers.
Set brass cap at cor. mkd. County Surveyor's T 25 S R 5 W
¼ S 21 S 22
1973
New BTs - 8" D.Fir N.31°E., 14.5 ft. scribed ¼ S22 CS BT.
12" D.Fir S.78°W., 38.4 ft. scribed ¼ S21 CS BT.

Found O.K. - Pieske, Herman - 3/5/1993 - 1993-0038

Douglas County Surveyors Office - Ed Monrean & Randall Smith - 7/1/97 - C.S. 64/75-22

Mon. Fd.- 2½" Brass cap on a 1½" O.D. iron pipe, protrudes 6" above ground. (1973)
3/4" I.R., bears S.30°W., .3' from BC/IP (1972)
Bt's Fd.- 8" now 13" dia. D.Fir, with a fully healed double blaze, bears N.31°E., 14.5' (agrees with rec.) 1973.
12" now 18" dia. D.Fir, with a fully healed double blaze, bears S.78°W., 38.4' (agrees with rec.) 1973.
New Accessories -
11" dia. Cedar, double blazed and scribed "¼ S22 CS BT", bears N.88°E., 7.5'.
18" dia. Madrone, double blazed and scribed "¼ S21 CS BT", bears N.11°W., 8.5'.

Found OK by K. Hoffine, Dec, 2001 - M137-29