

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec Cor for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 15, 16, 21 & 22, from which
A W.Oak 24" dia. bears S.24½°E., 177 lks. dist.
A W.Oak 20" dia. bears S.33°W., 295 lks. dist.
Made trench as per instructions.

Doug. County Surveyors Office - March 28, 1955 -
C.S. File 46/108

Found - 40" W.Oak S.24½°E., 177 lks. (116.8 ft.), scribe
marks visible of original survey & some scribe
marks made about 10 years later. Otherwise,
tree was destroyed.

Set - 1" x 36" Iron pipe with brass cap mkd. County
Surveyors Office, T25S R5W 16 15 1955.
21 22

From which:

R.Fir 10" bears S.56°W., 63.2 ft. mkd. T25S R5W S21 CSBT
R.Fir 16" bears S.12°E., 115.3 ft. mkd. T25S R5W S 22
CS BT.
R.Fir 8" bears N.22°E., 163.0 ft. mkd. T25S R5W S15 CSBT.
No trees of sufficient size available in NW quad.

Doug. Co. Surveyors Off. Vernon Tracy; Jack Heritage; V.
Perron - August 20-21, 1968 - C.S. File 49/124-100

Found - Orig. 40" W.Oak, alive S.24½°E., 116.8 ft. blaze
badly decayed.
10" now 16" D.Fir alive, S.56°W., 63.2 ft. healed
blaze and tag.
16" now 20" D.Fir, alive, S.12°E., 115.3 ft. healed
blaze and tag.
8" now 15" D.Fir alive, N.22°E., 163.0 ft. healed
blaze and tag.

No trace of I.P. and brass cap as recorded in 1955.

Set - Brass cap at cor. mkd. County Surveyors T25S R5W
(Set 6' steel fence post Office S 16|S 15
alongside brass cap) 1968 S 21|S 22

This cor. lies 150 ft. North of County Road.

Fd. Brass Cap by Donald Bentz, Feb. 1994 - M 118-30

Fd. Brass Cap by D.Bentz, Feb. 1995 - Vol. 18 Pg. 35

Fd. Ok - Douglas Co. Surveyors Office - Randall Smith &
Stephen Flause - 6/30/97 - C.S. 64/75-27 & C.S.64/79-9

Fd. OK June 1998 by D.Edwards - Subd. Vol. 19 Pg. 47