

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. Secs. 9, 10, 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 9, 10, 15 & 16, from which
A W.Oak 12" dia. bears S.34°E., 37 lks. dist.
A W.Oak 12" dia. bears S.81°W., 229 lks. dist.
A Y.Oak 20" dia. bears N.70½°E., 65 lks. dist.
A Y.Oak 18" dia. bears N.40°W., 97 lks. dist.

James W. Byron, Deputy; Milo E. Godfrey; Clete Putnam
April, 1960 - C.S. 49/124-57

Found - Orig. 12" now 28" W.Oak S.81°W., 151.1 ft. I open
& find good scribing "TS".
Orig. NW BT., down & mostly rotted, no scribing
found.

Orig. SE & NE BTs, now stump holes only.

Set brass cap at corner mkd: County Surveyors Office, 1960
S 9 S 10 T25S R5W
S 16 S 15

New BTs - 9" R.Fir bears S.30°E., 17.4 ft. scribed S15
T25S R5W CS BT.
19" R.Fir bears S.23°W., 27.1 ft. scribed S16 T25S
R5W CS BT.
10" W.Oak bears N.69°W., 42.8 ft. scribed S9 T25S
R5W CS BT.
9" R.Fir bears N.52½°E., 38.3 ft. scribed S10 T25S
R5W CS BT.

See CS File for sketch of cor. & relationship to fences.

Found & used, BLM dependent Resurvey, 1962. DCSO records
Volume 31, Page 13147-48

Fd BC, Robert Dolan, March 1992, Partition plat 1992-0024.

FD. Ok by Mark Heimburger, 12/2007 - M154-75