

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records Volume 9 Page 3789)

Set 1/4 sec. post, from which
A Y.Oak 5" dia. bears S.68 1/2°E., 7 lks. dist.
A Laurel, 10" dia. bears S.41 1/2°W., 52 lks. dist.

BLM Dependent Resurvey, Patrick J. Reynolds under Group #476
Survey July 25-August 30, 1962 (DCSO records Volume 31 Page
13148-49)

There is no remaining evidence of the original corner.
Set an I.P. 30" long 2 1/2" dia. 28" in the ground, with brass
cap marked: T. 25 S R 5 W

1/4
S 9 | S 10
1962 from which:
A Fir 14" dia. bears N.9°E., 139 lks. dist. marked
1/4 S10 BT.
A Fir 16" dia. bears S.87°W., 59 lks. dist. marked
1/4 S9 BT.

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - June 26, 97 - C.S. 64/75-15

Mon. Fd.- 3 1/4" brass cap on a 2 1/2" O.D. iron pipe protrudes 2"
above ground. 1962

Accessories Fd.-
14" now 25" dia. D.Fir, with a fully healed single
blaze N.9°E., 91.7' (agrees with rec.).
16" now 23" dia. D.Fir, with a fully healed single
blaze, bears S.87°W., 38.9' (agrees with rec.)
1962

New Accessories -
13" dia. D.Fir, double blazed and scribed "1/4 S10 CS
BT", bears N.63 1/2°E., 9'.
12" dia. D.Fir, double blazed and scribed "1/4 S9 CS
BT", bears N.51°W., 10'.