

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 3, 4, 9, & 10, from which
A W.Oak 7" dia. bears S.34°W., 40 lks. dist.
A W.Oak 9" dia. bears N.82½°W., 35 lks. dist.
A W.Oak 14" dia. bears N.45½°E., 91 lks. dist.
A Laurel, 14" dia. bears S.49¾°E., 118 lks. dist.

James W. Byron, Deputy; Milo Godfrey; Clete Putnam
April 20, 1960 - C.S. File 49/124-47

Found - Orig. 7" now 10" W.Oak S.34°W., 26.4 ft. I open &
find good scribing "T".
Orig. 14" now 30" W.Oak, shows old axe work, center
rotted, no scribing, N.45½°E., 60.1 ft.
Laurel stump that checks for SE BT.
No trace of NW BT found.
Also find stone with + on top, at corner.
Set brass cap at cor. mkd. County Surveyor's S 4 | S 3 T25S R5W
Office, 1960 S 9 | S 10
New BTs - 7" W.Oak bears S.54°W., 28.4 ft. scribed S 9 T25S
R5W CS BT.
7" W.Oak bears S.43°E., 18.0 ft. scribed S10 T25S
R5W CS BT.
5" W.Oak bears N.79°E., 6.8 ft. scribed S 3 CS BT.
5" W.Oak bears N.63½°W., 38.0 ft. scribed S 4 CS BT.

Found & used, BLM - 1962 Dependent Resurvey - DCSO records
Volume 31, Page 13149-50.

Carl Sweeden - For: James & C.J. Carlile - 2/2002 - M139-53

Found - 2½" BC on iron pipe up 1.5' and 1.5' west of 3 way
fence cor.
10" W.Oak BT, S.34°W., 26.4' now a depression.
Rotted trunk near by.
30" W.Oak BT now 24", N.45½°E 60.10' to face. Tree
rotten and hollow inside.
7" W.Oak BT, S.54°W., 28.4' now a depression of
root hole. Oak trunk. Laying nearby w/ tag
attached.
7" W.Oak BT S.43°E., 18.0' leaning north and dead.
No tag or sign of scribing
5" W.Oak BT N.79°E., 6.8' now oak stem approx. 3"
in dia. Laying down
5" W.Oak BT N.63½°W., 38.0' gone.
continued next page

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 5" W.Oak BT N.48°E., 17.5' scribed "S3 T25S R5W
BT" with tag
5" W.Oak BT N.55°E., 44.95' scribed "S4 T25S R5W
BT" with tag
8" D.Fir BT S.46°W., 17.45' scribed "S9 T25S R5W
BT" with tag
6" D.Fir BT S.43°E., 50.15' scribed "S10 T25S R5W
BT" with tag

Fd. BC as per M139-53 by D. Edwards - 3/2017 - M173-21