

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 440540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Section 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

W.F. Briggs, For: Briew & Archambauw - April 18, 1889  
Volume 1 Page 135-6

-----  
Set post center sec. 10, from which  
    Laurel, 12" dia. bears S.09½°W., 21 lks.  
    Fir 8" dia. bears S.51½°E., 19 lks.

Burton W. Holt, LS #418 for: Sun Studs, Inc. - Aug. 1983  
C.S. 58/252 and M 95 - 19

-----  
Set - 5/8" x 30" Iron rod with alum. cap mkd. T25S R5W  
      C ¼ S10 1983 LS 418.

From which:  
    15" Fir bears S.14°W., 3.1 ft. mkd. C¼ S10 BT.  
    9" Fir bears N.46°E., 25.0 ft. mkd. C¼ S10 BT.  
Corner lies 50 ft. East of logging road on W. slope. E-W  
fence lies 10 ft. North and N-S fence lies 15 ft. East.

Doug. County Surveyors Office - Larry E. Monrean, Deputy  
John Pike, and Witness: Danny Lang - Oct. 29, 1992 - C.S.  
File 64/32-10

-----  
Found - 5/8" Iron rod with alum. cap.  
        15" now 18" D.Fir with well healed single blaze,  
            bears S.14°W., 4.6 ft.  
        10" now 14" D.Fir with well healed double blaze  
            bears N.44°E., 24.5 ft.  
New BTs - 13" D.Fir double blazed and scribed "C¼ S10 CS BT"  
            N.36°W., 51.1 ft.  
        9" I.Cedar double blazed & scribed "C¼ S10 CS BT"  
            bears S.8°E., 22.1 ft.