

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3 of T26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853
(DCSO records, Volume 9 Page 3773-74)

Set post, cor. to secs. 34, 35, 2 and 3, from which
A Fir 10" dia. bears N.83¼°W., 96 lks. dist.
A Fir 11" dia. bears N.69¾°E. 13 lks. dist.
A Fir 12" dia. bears S.6¾°E., 144 lks. dist.
A Fir 10" dia. bears S.27½°W., 43 lks. dist.

BLM Dependent Resurvey, C. Albert White; Donald R. Beck
Group #502 - Survey May 1963 (DCSO records Vol 32 Pg 13361)

There is no remaining evidence of the original corner.
Set an I.P. 28" long 2½" dia. 22" in the ground, with brass
cap marked:

T 25 S R 5 W
S 34 | S 35
S 3 | S 2

1963

from which

A Fir 15" dia. bears N.35½°E., 228 lks. dist. mkd T25S
R5W S35 BT.
A Fir 10" dia. bears S.46°E., 223 lks. dist. mkd. T26S
R5W S2 BT.
A Fir 15" dia. bears S.84°W., 447 lks. dist. mkd. T26S
R5W S3 BT.
A Fir 15" dia. bears N.57°W., 529 lks. dist. mkd. T25S
R5W S34 BT.

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick,
Cadastral Surveyors and Robert H. Browning, Survey Tech,
under Group No. 2065 surveyed May 2004/April 2005 - (DCSO
records Vol. 57 Page(s) 22458)

The cor. of secs. 2, 3, 34, & 35, on the N. bdy. of the Tp.,
monumented with an iron post, 2½" dia., firmly set,
projecting 2" above the ground, with brass cap (properly) mkd
from which the remains of a BT mkd. by White and Beck

A sawed, decayed fir stump, 19" dia., bears S.80°W.,
297.3 ft., with no marks visible. (Record, S.84°W.,
295.0 ft.)

and new bearing trees

A fir, 5" dia., bears N.18°E., 37.9 ft., mkd. T25S R5W
S35 BT.
A fir, 17" dia., bears S.36½°E., 37.2 ft., mkd. T26S R5W
S2 BT.
A fir, 29" dia., bears S.81¼°W., 308.8 ft., mkd. T26S
R5W S3 BT.