

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W. H. Byars, Contract #152 dated June, 1871
(DCSO records Volume 9 Page 3805)

Set $\frac{1}{4}$ sec. post, from which
 A Fir 5" dia. bears N.2°E., 7 lks. dist.
 A Fir 5" dia. bears S.79°W., 12 lks. dist.

BLM Dependent Resurvey, C.Albert White; Donald R. Beck
Group #502, Survey, May 3-24, 1963 (DCSO records Volume 32
Page 13364-65)

There is no remaining evidence of the original corner.
Set an I.P. 28" long $2\frac{1}{2}$ " dia. 24" in the ground, with brass
cap marked:

$\frac{1}{4}$
S 34|S 35
T 25 S|R 5 W
1963

from which:

A Fir 10" dia. bears N.74 $\frac{1}{2}$ °E., 42 lks. dist. mkd. $\frac{1}{4}$ S35
BT.
A Fir 6" dia. bears N.63 $\frac{1}{4}$ °W., 198 lks. dist. marked
 $\frac{1}{4}$ S34 BT.

Fd. OK - Daniel Baker - for: Waggoner - 10/20/95 - M 119-75