

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Elder & Gile, Contract #31 dated April, 1853

-----  
Set post cor. to Secs. 22, 23, 26 & 27, whence  
A Fir 12" dia. bears S.54°W., 22 lks. dist.  
A Fir 12" dia. bears S.85°E., 20 lks. dist.  
A Fir 12" dia. bears N.32°E., 19 lks. dist.  
A Fir 15" dia. bears N.20°W., 16 lks. dist.

J.W. Cole, Deputy Co. Surveyor - L.H. Smick; P.D. Wolford  
Nov. 1920 - Vol. 3 Pg. 82; F.B. 49 Pg. 32; M 6-21

-----  
Found two orig. BTs broken off about 6 ft. above the ground.  
Old scribe marks visible. Other trees down & slid down hill.  
Set a Maple stake 6" x 6" x 40" from which:  
Original BTs bear N.33½°E., 12.6 ft.  
S.87°E., 13.2 ft.

New BTs - A Fir 36" dia. bears N.49¼°E., 50.3 ft.  
A Fir 50" dia. bears N.33°W., 44.0 ft.  
A Fir 24" dia. bears S.42½°W., 16.6 ft.  
A Fir 24" dia. bears S.49°30'E., 36.6 ft.  
(See also Briggs 1889 corner in Volume 1 Page 136)

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete  
Putnam - May & June 1960 - C.S. File 49/124-65

-----  
Found - Now 30" stump S.42½°W., 16.6 ft. shows good bark  
scribing "BT".  
Now 30" stump N.49¼°E., 50.3 ft. bark gone, no  
scribing.  
30" Fir stump S.49½°E., 36.6 ft. shows good bark  
scribing.

Corner fence post at Sec. cor. Set brass cap alongside & mkd.  
County Surveyors Office 1960 S22 | S23  
T25S R5W S27 | S26

New BTs - 5" R.Fir bears S.68°W., 12.7 ft. scribed S27 T25S  
R5W CS BT.  
10" R.Fir bears N.6°W., 43.9 ft. scribed S22 T25S  
R5W CS BT.

Ken Hoffine - For: Lone Rock Timber Co. - Gary Angiolet &  
Iginaco Roman - 9/2/2009 - C.S. File 65/66-37

-----  
Found - D.Fir bears N.8¾°W., 43.0 ft. (rec. N.6°W., 43.9  
ft.) healed face & tag.  
1960 County BCIP 0.3 ft. above ground.  
New - 22" D.Fir bears N.69¾°E 88.2 ft. we scribe T25S R5W  
S23 BT and tag. continued next page

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

13" D.Fir bears S.52 $\frac{3}{4}$ °E., 9.8 ft. we scribe T25S R5W S27 BT and tag.  
26" D.Fir bears S.66 $\frac{1}{4}$ °W., 12.3 ft. we scribe T25S R5W S26 BT and tag.  
Note - Corner lies on northeast slope approx. 50 feet S.46°W., from draw. A fenceline is north 12 ft. from section corner. Fence line runs northeast and west.