

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 14, 15, 22 & 23, from which
A Y.Oak 24" dia. bears S.10¾°E., 1009 lks.
A Y.Oak 20" dia. bears S.56¾°W., 226 lks.
A Y.Oak 16" dia. bears N.75°W., 142 lks.
A W.Oak 14" dia. bears N.35¾°E., 183 lks.

James W. Byron, Deputy Co. Surveyor - Milo Godfrey; Clete Putnam - May & June, 1960 - C.S. File 49/124-61

Found - Orig. 14" now 30" W.Oak opened years ago, shows good scribing "S11" N.35¾°E., 120.8 ft.
Low cut 30" B.Oak stump, checks bearing & dist. for NW BT.
No trace of SE or SW BTs found.

Set brass cap at cor. mkd: County Surveyor's Office 1960
S15 | S14 T25S R5W
S22 | S23

New BTs - 12" R.Fir bears N.31°W., 63.9 ft. scribed S15 T25S R5W CS BT.
9" W.Oak bears S.86°E., 20.2 ft. scribed S23 T25S R5W CS BT.
10" W.Oak bears S.47°W., 63.8 ft. scribed S22 T25S R5W CS BT.
14" Laurel bears N.52°E., 4.0 ft. scribed S14 T25S R5W CS BT.

Doug. Co. Surveyors Office - J. Heritage; G.E. Commins; January, 1973 - C.S. File 56/25-2

Found - 1960 renewal trees OK. Did not find brass cap.
Set - Brass cap mkd. County Surveyors T 25 S R 5 W
Office S 15 | S 14
1973 S 22 | S 23

Douglas County Surveyors Office - Ed Monrean & Randall Smith - 7/1/97 - C.S. 64/75-21

Mon. Fd.- 2½" Brass cap on a 1½" O.D. iron pipe protrudes 18" above ground. (1973)
A large stone measuring 20" x 9" x 6" is laying flat on top of ground along east edge of BC/IP.
Bt's Fd.- 12" now 24" dia. D.Fir stump cut low no blazes visible, bears N.31°W., 63.9' (agrees with rec.) 1960

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

14" now 18" dia. Madrone, with a fully healed blaze, bears N.52°E., 4' (agrees with rec.) 1960
9" now 11" dia. dead W.Oak, with a fully healed double blaze, bears S.86°E., 20.2' (1960)
10" now 20" dia. W.Oak, with a fully healed blaze, bears S.47°W., 62.3' (rec. S.47°W., 63.8' dist. is a slope measurement) 1960.

New Accessories -
12" dia. D.Fir, double blazed and scribed "T25S R5W S15 CS BT", bears N.25°W., 86.9'.
16" dia. W.Oak, double blazed and scribed "T25S R5W S22 CS BT", bears S.8°W., 100.5'.

Corner lies 4' west of a N-S fence line.