

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Secs. 10, 11, 14 and 15, from which
 An Ash 15" dia. bears N.24¾°W., 112 lks. dist.
 An Ash 14" dia. bears S.76¼°W., 150 lks. dist.
Made trench as per instructions.

H.L. Eppstein, F.C. Frear; Jas. Wolford; G.W. Milam
Aug. 1934 - "Old" Corner renewal book, Vol. 1 Pg. 54
(No other source record found. 8/1991 V.L.)

Reestablished from original BT. to wit, Ash 36", marks still
visible bears S.76¼°W., 99.0 ft. I remark this tree. Also an
 Ash 10" N.18¾°W., 61.7 ft.
 Ash 14" N.13°E., 97.0 ft.
Set a ¼" x 1¼" x 36" Spring and an 18" Rasp for corner.

James W. Byron, Deputy; Milo E. Godfrey; Clete Putnam
April 20, 1960 - C.S. File 49/124-56

Found - Auto Spring & squared rock at corner & stump of
 Eppstein's Ash N.13°E., 97.0 ft. shows good
 scribing.
 Also stump of original SW BT.
Set brass cap alongside Auto Spring & mark: County Surveyors
 Office, 1960 S10|S11
 S14|S14 T25S R5W
New BTs - 8" Ash bears S.76°W., 98.5 ft. scribed S15 CS BT.
 5" Ash bears N.30½°W., 57.0 ft. scribed S11 CS BT.
No trees near to NE or SE.

Doug. Co. Surveyors Office - R.B. Kimberling; P.L. Earle
July 26, 1977 - C.S. File 59/38-7

Found - A 1" I.P. with 1960 DCS0 brass cap facing south,
 set 1" below ground, properly mkd.. Removed
 BC and bent I.P.
 Sandstone (squared) rock on south side of BC 13" x
 10"x5", 8" below ground w/1" X chiseled on top.
 An arched auto spring 31½x1½x3/8" 8" below ground.
(Cont. Next page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Found -	Burned remains of Ash stump bears S.76¼°W., 99.0 ft. southerly portion of a 2 forked Ash is rotted away, remains bear N.14°E., 97.0 ft. (Rec.N.13°E) An 11" Ash stump bears S.76°W., 98.5 ft. A 5" now 11" Ash bears N.30½°W., 56.6 ft. Open upper blaze & find fragmentary scribing.
Set -	A new brass cap on a 36" I.P. 1" dia. 8" below ground stamped County Surveyors Office T25S R5W S10 S11 S15 S14 1977.
Reset -	Sandstone rock on South side of BC 1.0 ft. below ground. Auto spring on North side of BC 8" below ground.
New BTs -	An Ash 10" bears N.14°E., 97.9 ft. mkd. "25S R5W S11 CS BT". A 2 forked Ash, 18" measured below fork, bears S.68°W., 146.8 ft. mkd. "T25S R5W S15 CS BT". A 3 forked Ash, 25" measured below forks, bears S.80¾°E., 218.5 ft. mkd. T25S R5W S14 CS BT.
Douglas County Surveyors Office - Randall Smith & Stephen Flause - June 23, 1997 - C.S. 64/75-27 -----	
Fd. OK - Added BT tags to 4 live BT's	