

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post corner to Secs. 2, 3, 10 and 11, from which
A Y.Oak 12" dia. bears N.54°E., 17 lks. dist.
A Y.Oak 20" dia. bears N.86°W., 49 lks. dist.
A Y.Oak 16" dia. bears S.64°W., 82 lks. dist.
A W.Oak 12" dia. bears S.23°E., 53 lks. dist.

James W. Byron, Deputy - Milo Godfrey; Clete Putnam
April, 1960 - C.S. File 49/124-49

Found - Orig. 12" now 22" W.O. S.23°E., 35.0 ft. I open &
find good scribe marks "S".
Orig. 20" now rotted B.O. stump, shows old axe work,
N.86°W., 32.3 ft.
No trace of orig. NE or SW BTs found.
Also find 2" x 3" x 24" stone at corner.
Set brass cap at cor. mkd. County Surveyor's S 3|S 2 T25S R5W
Office 1960 S10|S11
Reset corner stone alongside brass cap.
New BTs - 9" R.Fir bears S.75°E., 23.3 ft. scribed S11 T25S
R5W CS BT.
7" R.Fir bears S.7°W., 41.7 ft. scribed S10 T25S
R5W CS BT.
8" R.Fir bears N.67°W., 14.3 ft. scribed S3 T25S
R5W CS BT.
11" R.Fir bears N.30°E., 49.7 ft. scribed S2 T25S
R5W CS BT.

Douglas county Surveyors Office - Randall Smith & Stephen
Flause - June 5, 1997 - C.S. 64/75-8

Mon. Fd.- 2½" dia. Brass cap on a 1½" O.D. iron pipe protrudes
14" above ground. (1960)
2"x3" topped stone protrudes 7" above ground. lies
along NW side of BC/IP no marks visible
(source unknown).

Accessories Fd.-

12" now 23" dia. W.Oak, with a previously opened
nearly healed, scribing visible "S", bears
S.23°E., 35' (agrees with rec.) OBT.
7" now 14" dia. D.Fir, with a fully healed double
blaze, bears S.7°W., 41.7' (agrees with rec.)
1960

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

9" now rotted remains of a D.Fir stump, rec.
"S.75°E., 23.3'. 1960
11" now rotted remains of a D.Fir stump rec.
"N.30°E., 49.7'". 1960
1960 NW BT now gone
No other OBT's found
New Accessories -
13" dia. Madrone, double blazed and scribed "T25S
R5W S10 CS BT", bears S.22½°W., 38.3'.
3" dia. D.Fir, double blazed and scribed "X BT",
bears N.54°E., 15.8'.
Corner lies approx. south 65' from a gravel road.

DCS0-GIS Corner visitation - 8/5/2011 - Typed: 1/24/2011 -
C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK