

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35; & Sec. 2 of T.26-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set gr. sec. post, from which

A Y.Oak 7" dia. bears N.73½°W., 120 lks. dist.

A Y.Oak 11" dia. bears N.70°W., 213 lks. dist.

G. Robert Lecklider - For: Bernard Grubbe, Sept. 1961
M 21-29

Found - Oak stump S.73½°W., 120 lks. BT destroyed by logging
Renewed from notes I had from previous occasion.

Set - Steering Wheel shaft.

24" P.Pine N.07°W., 40.7 ft.

14" Fir S.65°W., 37.4 ft.

Bureau of Land Management - C. Albert White; Donald R. Beck
Cadastral Surveyors - May 1963 - DCSO recs Vol 32 Pg 13360-61

Found - Steel shaft 30" long ¾" dia. protruding 10" above
ground, firmly set, from which bearing trees
mkd. by Lecklider:

A Fir 25" dia. bears N.11°W., 65 lks. dist., mkd
¼ S35 T25S R5W BT, on a double blaze.

A Fir 11" dia. bears S.80½°W., 57 lks. dist. mkd.
¼ S2 T26S R5W BT, on a double blaze.

At the corner point

Set an iron post 28" long, 2½" dia. 22" in the ground with
brass cap mkd. T 25 S R 5 W

¼ S 35

S 2

T 26 S

1963

Deposit the steel shaft alongside the iron post.

Fd. OK - Daniel Baker - for: Waggoner - 10/20/95 - M 119-75

Fd. & used on BLM rehabilitation of certain corners, Timothy
J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying
Tech., under Group #2000, 2100, & 2300, Surveyed June 2004, -
(DCSO records Vol. 55 Page(s) 21498) See 2008 plat

BLM Dependent resurvey by Timothy J. Moore, A. Bert Skeesick,
Cadastral Surveyors and Robert H. Browning, Survey Tech,
under Group No. 2065 surveyed May 2004/April 2005 - (DCSO
records Vol. 57 Page(s) 22460-1)

The ¼ sec. cor. of secs. 2 & 35, on the N bdy. of the **(cont.)**

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35; & Sec. 2 of T. 26-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tp., monumented with an iron post, 2½" dia., firmly set, projecting 10" above the ground (alongside of which is a geared steering shaft, 1" dia., firmly set, projecting 18" above the ground), with brass cap (properly) mkd.

from which the remains of BTs mkd. by Lecklider, in 1961

A sawed fir stump, 26" dia., bears S.60¼°W., 37.0 ft., with a healed double blaze. (Rec. S.80½°W., 37.6 ft.)

A sawed pine stump, 41" dia., bears N.11°W., 41.1 ft. with a healed blaze. (Record, fir, 42.9 ft.)

and new bearing trees

A fir, 10" dia., bears N.23¼°E., 21.3 ft. mkd. ¼ S35 BT.

A fir, 12" dia., bears S.63¾°W., 22.8 ft. mkd. ¼ S2 BT.

Corner is located 1.0 ft. W. of a woven wire fence, with fences extending north and south.