

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post, cor. to secs. 35, 36, 1 and 2, from which
A Fir, 24" dia. bears S.42½°E., 7 lks. dist.
A Laurel, 12" dia. bears S.46°W., 83 lks. dist.
A Laurel, 10" dia. bears N.7½°E., 96 lks.
A Laurel, 20" dia. bears N.40½°W., 88 lks.

James W. Byron, Deputy - Milo Godfrey; Clete Putnam - June 21, 1960 - C.S. File 49/124-68

Found - Orig. 24" now 44" Fir S.42½°E., 4.6 ft. I open and find good scribing.
Also find Laurel trees, now mostly rotted that check for orig. NW & NE BTs.
No trace of orig. SW BT found.
Set - Brass cap at corner mkd. County Surveyor's Office, 1960

S35	S36	T25S
S 2	S 1	T26S R5W

New BTs- 18" R.Fir bears N.53°E., 12.4 ft. scribed S36 T25S R5W CS BT.
11" Maple bears N.37°W., 10.1 ft. scribed T25S R5W S35 CS BT.
10" R.Fir bears S.22°W., 59.0 ft. scribed T26S R5W S 2 CS BT.

Bureau of Land Management - A. White; D. Beck, May 3-24, 1963 - DCSO Records Volume 32 Pages 13362-63

CORNER REPORT ONLY
Found - Iron post 36" long 1" dia. protruding 18" above ground, firmly set w/brass cap properly mkd.
A Madrone snag (orig) 12" dia. bears N.7½°E., 96 lks. dist. mkd. with a rotted blaze.
A Fir 47" dia. bears S.42½°E., 7 lks. dist. mkd. with illegible scribing on an opened blaze.
A Madrone snag 22" dia. bears N.40½°W., 88 lks. dist. mkd. with a rotted blaze. (orig.)
A Fir 17" dia. bears N.51°E., 19 lks. dist. mkd. with a pitched over blaze. (1960 Byron)
A Fir 10" dia. bears S.20°W., 89 lks. dist. mkd. with a pitched over blaze. (1960 Byron)
A Maple, 10" dia. bears N.37°W., 16 lks. dist. mkd. T25S R5W S35 CS BT, on open blaze. (1960)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. 35 & 36; 1 & 2 of T26-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyor's Office - Randall Smith; Terrie Franssen - June 28, 1990 - C.S. File 64/9-13

-
- Found - A 2½" dia. 1960 DCS0 brass cap on a 1¼" O.D. Iron pipe protruding 17" above ground.
- 24" now 54" dia D.Fir with a fully healed previously opened blaze bears S.42½°E., 4.6 ft. (Orig. BT.) Agrees W/record.
 - 10" now 12" dia. down & rotted Madrone bears N.7½°E 63.4 ft. (original BT.)
 - 20" now 40" dia. 25 ft. high madrone snag with a rotted center bears N.40½°W., 55.5 ft. (Record N.40P°W., 58.1 ft.) Original BT.
 - 18" now 27" dia. D.Fir with a fully healed, double blaze, bears N.51°E., 12.5 ft. (agrees w/BLM)
 - 11" now 16" dia. Maple with a fully healed double blaze, bears N.37°W., 10.1 ft. (agrees w/rec)
 - 10" now 12" dia. down D.Fir with a fully healed double blaze root hole bears S.20°W., 58.7 ft.
- New BT - 10" dia. D.Fir double blazed & scribed "T26S R5W S2 CS BT". bears S.16½°W., 50.5 ft.