



PRIMARY CORNER DESCRIPTION Sec Cor for 2, 1, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Found - 1" I.P. with brass cap 10" above ground & firmly set, properly stamped.  
Orig. Oak 24" now 30", now uprooted & partially decayed. The root hole of the tree bears S.17½°W., 60.7 ft. We open tree & find good reverse scribing "BT", actual face rotted out. All other orig. BTs are down & badly decayed.  
An Oak 10" now 17" bears N.16°W., 27.4 ft. Tree has well healed double blaze.  
A Madrone 10" now 12" bears N.38¼°E., 33.8 ft. Blaze & scribing have been destroyed.  
A R. Fir 10" now 12" bears N.50°E., 20.4 ft. Tree has well healed double blaze.  
A R. Fir 12" now 16" bears S.34°W., 12.0 ft. Tree has well healed double blaze. We partially open & find scribing "S11" (Rec. "S2")  
A R. Fir 8" now 10" bears S.62°E., 20.1 ft. to center of base. (Rec. 21.2 ft. checks center trunk breast height) Tree has well healed double blaze.  
Fence cor. bears N.72°W., 18.4 ft. (Rec. 19') Fence runs North and West.

FD BC by Robert Dolan, July 1994 - M 120-61

Douglas County Surveyors Office - Randall Smith & Stephen Flause - July 29, 1997 - C.S. 64/71-26

-----  
Mon. FD.- 2½" brass cap on a 1½" O.D. iron pipe, protrudes 10" above ground. (1960 DCS0)  
Bt's Fd.- 15" Y.Oak, now root hole rec. "S.75°E., 3.3'" OBT  
20" Y.Oak, now root hole rec. "S17½°W., 60.7'" OBT  
10" now down and rotted Oak, no scribing visible root hole, bears N.16°W., 27.4'.  
10" now 12" dia. dead madrone, with a previously opened unhealed axe work, bears N.38¼°E., 33.8'.  
12" now 18" dia. D.Fir, with a fully healed double blaze, bears S.34°W., 12'.  
10" now 13" dia. D.Fir with a fully healed double blaze, bears N.50°E., 20.4'.  
8" now 8" dia. down and rotted D.Fir, with a fully healed double blaze, root hole bears S.62½°E., 21.2'.

(Cont. Next Page)

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec Cor For 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New Accessories -

19" Madrone, double blazed and scribed "T25S R5W S1  
CS BT", bears N.37½°E., 55.5'.

DCSO BC/IP NW COR DLC 43, bears North 36.7'.

13" W.Oak, with a NE facing blaze scribed "NW DLC 43  
CS BT", bears N.19°W., 33.3'.

Fd. ok by Carl Sweeden - 9/1998 - M 130-37

Fd. OK by Carl Sweeden - May 2001 - LP 2001-0053