

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set 1/4 Sec. post, from which
 A Y.Oak 14" dia. bears N.8 1/2°W., 32 lks. dist.
 A Y.Oak 12" dia. bears N.58 1/2°E., 88 lks dist.

Burton W. Holt for: Sun Studs, Inc. - July, 1984
C.S. File 58/298 and M 97-24

Set - 5/8" x 30" Iron Rod with 2" alum. cap marked
 "T25S R5W 1/4 S2 S1 L.S. 418 1984".
New BTs - 11" W.Oak bears N.21°E., 24.4 ft. which I face &
 scribe "1/4 S1 BT".
 12" D.Fir bears S.35°W., 12.2 ft. which I face &
 scribe "1/4 S2 BT".
Corner lies on a west slope, 915 ft. west of a N-S fence.

FD BC by Robert Dolan, July 1994 - M 120-61

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - June 5, 1997 - C.S. 64/75-7

Mon. Fd.- 2" dia. Alum. cap on a 5/8" I.R. protrudes 2" above
 ground. (1984)
Accessories Fd. -
 11" now 12" dia. W.Oak, with a partially healed
 single blaze, illegible scribing visible,
 bears N.19°E., 24.4' (Rec. N.21°E., 24.4')
 1984.
 12" now 17" dia. D.Fir, with a fully healed single
 blaze, bears S.35°W., 12.2' (agrees with rec.)
 1984
New Accessories -
 7" dia. Madrone, double blazed and scribed "1/4 S2 CS
 BT", bears N.16°W., 37.4'.
 13" dia. Madrone, double blazed and scribed "1/4 S1 CS
 BT", bears S.61°E., 19.2'.
Corner lies 9' west of a N-S fence line on a west slope.

Found Ok by Douglas Co. Surveyors Office - Randall W. Smith &
Stephen J. Flause - 11/26/1997 - C.S. File 64/79-9