

TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - 7-8-97 - C.S. 64/75-24

Mon. FD.- 2½" dia. Brass cap on a 1½" O.D. iron pipe,
protrudes 12" above ground. 1960 BC/IP is loose.
Bt's Fd.- 20" now 24" dia. 4' high rotted D.Fir stump, with a
fully healed blaze, bears N.9°E., 27.2'
(agrees with 1960 rec.)
19" now 29" dia. 2' high D.Fir stump, with a fully
healed blaze, bears S.39°W., 25' (agrees with
1960 rec.)
16" now 38" dia. 2' high Oak stump, has a rotted out
center and shows evidence of being previously
opened, bears N.54°W., 63.4' (agrees with
orig. rec.) OBT
13" D.Fir, with an unhealed single blaze, scribing
visible "¼ S25 BT", bears S.50 ¾°E., 20.1'
(agrees with rec.) 1966
Mon. Set- reference plumb position of BC/IP, removed BC/IP
measured 36" long set back at referenced
position protrudes 6" above ground.
New Accessories -
16" dia. Madrone, double blazed and scribed "¼ S25
CS BT", bears S.79°W., 35.4'.
10" dia. D.Fir, double blazed and scribed "¼ S24 CS
BT", bears N.58½°E., 79.8'.
Corner lies at the intersection of E-W and S running fence
line.

Fd. OK - by Janet Lundeen - Sept. 1997 - 1997-0099A&B

DCS0-GIS Corner visitation - 8/9/2004 - Typed: 1/24/2011 -
C.S. File 67/33-1

Monument - 1.25" BC/IP
Comment - OK