TOWNSHIP 25 RANGE 05 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 24; & 19, T.25-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - James Freeman, Contract #1 dated May, 1851 (DCSO records Volume 9 Page 3730)

Set ¼ Sec. post, from which
A W.Oak 12" dia. bears N.46½°W., 115 lks. dist.
A W.Oak 11" dia. bears S.19°E., 98 lks. dist

BLM Dependent Resurvey, Irving Zirpel; Lynn Roseberry; Harold Corbin, under Special Instructions dated July 8, 1957 and July 15, 1958 (DCSO Records Vol. 29 Page 12265)

The ¼ sec. cor. of secs. 19 and 24, determined at record bearing & distance from the only remaining original brg. tree:

A W.Oak 22" dia. bears S.19°E., 98 lks. with scribe marks ¼ S BT visible on open blaze.

At the corner point set:

An iron post 28" long 1½" dia. 24" in the ground with brass cap marked: T25S

¼

R5W | R4W

S 24 | S 19

1957

from which:

A Fir 11" dia. bears S.81°E., 67 lks. mkd. ¼ S19 BT
A Fir 10" bears S.70¼°W., 30½ lks. mkd. ¼ S24 BT.

The cor. falls at the foot of N.slope & by fence extending N & S.

BLM dependent Resurvey, James Jelley; Wayne Rogers, Group #1084, Special Instructions dated Dec. 14, 1981. Survey Jan. 8, 1982 - June 22, 1982.(DCSO records Vol. 45 Pg. 17516)

Found - 1957 BLM brass cap.
Orig., W.Oak 24" dia. bears S.19°E., 98 lks. with scribe marks BT visible on opened blaze.
1957 BT, A Fir 19" dia. bears S.82½°E., 67 lks. with healed blaze.
1957 BT, a sawed Fir stump 18" dia. bears S.70¼°W., 30½ lks. with healed blaze.

New BT - A Fir 8" dia. bears S.56½°W., 34½ lks. dist. mkd. ¼ S 24 BT.

Fd. BC & 3 BTs by Ken Hoffine, 7/2010 - M157-35