TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 041030

PRIMARY CORNER DESCRIPTION SW Cor. Watson DLC #41

Alias 062040 Description SE Cor. Tanner DLC #62
Alias Description
Alias Description
Alias Description

Original - Addison R. Flint, Contract #28 dated April, 1854

Set a post, from which
A B.Oak 18" dia. bears N.30°E., 252 lks.
Also dug quadrangular trench with stone in center.

Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; Mike Stone; Mike Darby - April 29, 1964 - C.S. File 49/123-122

Found - 57" B.Oak N.30°E., 166.3 ft., opened and found reverse scribing "62".
Set brass cap at cor. mkd: County Surveyor's Office 1964 T25S R6W SE DLC 62|SW DLC 41
New BTs - 16" W.Oak S.69°E., 77.9 ft. mkd: SW DLC 41 CS BT.
12" W.Oak N.87°E., 59.0 ft. mkd: SE DLC 62 CS BT.
A fence corner (fences East & North) bears East approx. 75 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 1/15/2002 - C.S. File 66/32-8

Found - 1964 DCSO brass cap iron pipe, protrudes 12" out of ground. Corner lies 13' South of an E-W fence line.
OBT now gone
1964 SE BT now gone
12" now 13" dia., W.Oak with an unhealed rotted blaze, partial illegible scribing visible. Rescribe high on a single blaze "SW 41 BT" bears N.87°E., 59.0 ft. (1964)
New - 10" dia., Madrone double blazed & scribed "SW DLC 41 CS BT" bears N.71°E., 66.4 ft.
5/8" I.R. "LS2752" bears N.79°E., 76.4 ft. M139-31
22" dia., I.Cedar double blazed & scribed "SE DLC 62 CS BT" bears S.29°W., 24.8 ft.
Compass decl. 17½°E.