

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION NW Cor. Medley DLC #46

Alias 047010 Description NE Cor. Dodge DLC #47  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint - Contract #28 dated April, 1854  
-----

Set post, from which

A W.Oak 8" dia. bears N.60°W., 75 lks.

A B.Oak 20" dia. bears N.5°E., 109 lks.

NOTE - BTs described for NE cor. of DLC #47 are as follows:

A W.Oak 8" dia. bears N.25°W., 299 lks.

A B.Oak 20" dia. bears N.3°E., 374 lks.

Wm. F. Briggs, County Surveyor - For: Scotch Company  
Jan. 29-30, 1892 - Volume 1 Page 203  
-----

Found one of the orig. BT standing, marks plain, except No. of Cl had been omitted by the Dep Sur. I put C 47 on the BT and established the N.E. Cor of Cl 47 by setting a post 4 ft. long 4" square, 24" in the ground & rock beside, 18"x6"x4", marked C 47 C.S. from which:

Orig. BT, W.Oak 14" dia. bears N.14°W., 299 lks. (The orig. brg. was incorrect, to wit, N.25°W., 299 lks.)

The B.Oak called for was standing but had no marks on it. I blazed & marked the intended BT, to wit, B.Oak 20" dia. bears (?)1½°E., 370 lks. mkd. C.47 CS BT.

Milo E. Godfrey, Deputy - Vernon Tracy; Clete Putnam  
Sept. 5, 1961 - C.S. File 49/123-3  
-----

Found - Pile of broken sandstone rocks at corner.  
W.Oak stump now 36" N.14°W., 197.3 ft.-found scribing "CS BT" facing N.82°E. South portion of stump gone.

Stump hole with portions of Oak stump in place N.1½°E., 244.2 ft. Too far gone to find any markings.

Set Iron pipe with brass cap mkd: County Surveyors Office 1961

T25S R6W  
NE DLC 47|NW DLC 46

Pipe set in mound of rocks.

New BTs - 8" W.Oak N.80°E., 21.0 ft. mkd. DLC 46 N.W. C. CSBT.  
12" W.Oak N.6°W., 153.3 ft. mkd: T25SR6W DLC #47 NEC CS BT.

Fence cor. bears S.70°W., 6 ft. Fences South and East.

Found OK by Edwards Aug. 1996 - Land Partition 1996-0074 A,B

Cont. next page

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 046010

PRIMARY CORNER DESCRIPTION NW COR MADLEY DLC #46

Alias 047010 Description NE COR DODGE #47  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause  
- Nov. 20, 1997 - C.S. 64/78-29  
-----  
Mon. Fd.- 2½" dia. brass cap on a 1½" O.D. iron pipe  
protrudes 5" above ground. A loose mound of  
stone is around base of BC/IP one stone has  
an etched line.  
Bt's Fd.- 8" now double trunked W.Oak, with a fully  
healed single blaze on eastern 13" trunk,  
center of blazed trunk bears N.77°E., 21'  
(rec. N.80°E., 21') 1961.  
12" now 24" dia. W.Oak, with a fully healed  
single blaze, bears N.6°W., 153.3' (agrees  
with rec.)1961.  
30" dia. 3' high rotted oak no blazes or  
scribing visible, bears N.14°W., 197.3'  
(agrees with ren. records) OBT see vol. 1  
pg. 203.  
Root hole bears N.1½°E., 244.2' (agrees with  
ren. records) OBT?  
New Accessories -  
5/8" I.R. protrudes 5" above ground, bears  
N.9½°E., 200.2'.  
Fence corner bears S.70°W., 6'.