

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 047040

PRIMARY CORNER DESCRIPTION SSF Cor. Dodge DLC #47

Alias 048030 Description Int. NW Cor. Williamson DLC #48  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1854

-----  
Set post, from which

A B.Oak 15" dia. bears N.40°E., 114 lks.

A W.Oak 12" dia. bears N.80°W., 38 lks.

-----  
Wm. Briggs For: The Scotch Company - January 1892  
Volume 1 Page 202

-----  
One of the original BTs was standing, to wit:

12" W.Oak bears N.80°W., 38 lks..

The post & the other BT has rotted & fell down. I set a  
new post 3½ ft. long 4" square 24" in the ground mkd. C 47  
C.S., from which

New BT - W. Oak 8" dia. bears N.28°E., 58 lks. mkd.

C 47 C.S B.T.

-----  
Ben B. Irving - Dep. Co. Surveyor - N.E. Richardson; James  
McHugill - August 1938 - M 11-10 and C.S. File 37/198

-----  
This cor. is located at an anchor post & fence corner.

The bearing trees as set by Briggs were identified & checked  
for bearing & distance. One had been cut & sprouted but  
when the old stump was chopped out, the scribe marks were  
plain. Drove a ¾" x 36" Iron pipe for the corner from which:

An Oak 8" dia. bears S.24°E., 16.6 ft.

An Oak 18" dia. bears N.12°W., 23 ft.

Both blazed & scribed Cl. 48 C.S.B.T.

-----  
Milo E. Godfrey, Dep. Co. Surveyor - Wm. Stoffel; M. Stone  
M. Darby - April-May, 1964 - C.S. File 49/123-117

-----  
Found - ¾" I.Pipe 4" below present ground surface.

9" W.Oak S.24°E., 16.6 ft. very plain scar.

New BT - 18" D.Fir S.71°E., 36.4 ft. mkd. Int. L DLC 48 CSBT  
Corner at old fence corner, traces of old fences west &  
north.

-----  
Found July, 1983, R. Dolan - M 94-50