

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 047050

PRIMARY CORNER DESCRIPTION Int. SE Cor. I. Dodge DLC #47

Alias <u>048020</u>	Description <u>NNW Cor. Williamson DLC #48</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Original - Addison R. Flint, Contract #28 dated April, 1854 ----- Set stone post, 15 x 6 x 3, from which A W.Oak 20" dia. bears S.15°W., 48 lks.</p>
<p>Wm. F. Briggs - For: The Scotch Company, Jan. 1892 Volume 1 Page 202 ----- The original BT has been cut down. I made a new post 4 ft. long 4" square 24" in the ground, mkd. C.47 C.S., from which I mark a W.Oak 40" dia. bears S.15°W., 54 lks. mkd. C47 C.S. BT.</p>
<p>Ben B. Irving, Deputy Co. Surveyor - N.E. Richardson; James McHugill - August 1938 - M 11-10 and C.S. File 37/198 ----- Location identified from an Oak stake bearing correct scribe marks. This evidently the corner as renewed by Briggs in 1892. Although the BTs are down and butt sections burned off. Checks for bearing & distance. Drove a ¾" Iron pipe alongside. Blazed & scribed: An Oak 42" dia. S.60°W., 44.0 ft.</p>
<p>Milo E. Godfrey, Deputy Co. Surveyor - Wm. Stoffel; M. Stone M.Darby - April 1964 - C.S. File 49/123-116 ----- Found - ¾" Iron pipe at corner. 46" W.Oak S.60°W., 44.0 ft., small portion of scribe mark visible in not completely covered blaze. New BT - 18" W.Oak N.74°W., 71.1 ft. mkd."Int. L DLC 47 CSBT" Cor. is in E & W fence line 5 ft. East of fence corner. Fences East, West and South.</p>
<p>Found OK, 7/83, R. Dolan - M 94-50</p>
<p>Fd. Ok by D. Edwards 4/2005 - M147-52 & 2005 - 0041A&B</p>
<p> </p>