

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 050020

PRIMARY CORNER DESCRIPTION N NW Cor. Stephens DLC #50

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set post, from which
 A B.Oak 18" dia. bears S.45°E., 62 lks. dist.
 Raised mound with trench as per instructions.

Wm. Briggs; (Thiel ?) For Charles McGee, March 31, 1886
DCSO file, Volume 1 Page 75

Set post & rocks 8x6x4 for N Cor of E. Stephens DLC.

Milo E. Godfrey, Dep. Co. Surveyor - Vernon R. Tracy; M.
Stone - July, 1962 - C.S. File 49/123-14

Found - Two rocks set by Wm. Thiel in 1886. One rock mkd.
 "┌".
 B.Oak now 30" S.45°E., 40.9 ft. This tree had been
 opened years ago, probably by Thiel. I cut open
 again, but find center rotted away. No scribing
 found.

Set brass cap at cor. mkd: County Surveyors Office, 1962
 T 25 S R 6 W. N NW Cor. DLC 50

New BTs - 10" W.Oak S.12°W., 7.4 ft. mkd: "N NW DLC 50 CSBT.
 15" W.Oak N.77°W., 31.6 ft. mkd: "N NW DLC 50 CS BT

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J.
Flause - 2/4/98 - C.S. File 64/79-18

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe,
 protrudes 12" above ground. 1962
above A stone with top measuring 6"x8" protrudes 2"
ft., ground is found Northeast of BC/IP 0.6
 no marks visible on top. 1886
 23" now 26" dia., 8 ft. high Oak rotted Oak snag,
 no scribing visible, bears S.45°E., 40.9 ft.
 (Agrees with rec.) OBT
 10" now 10" dia., W.Oak with a partially healed
 double blaze, scribing visible "NNW" bears
 S.12°W., 7.4 ft. (Agrees with rec.) Tree is
 dead. 1962
 15" now 18" dia., W.Oak with a fully healed double
 blaze, bears N.77°W., 31.6 ft (Agrees with
 Rec.) 1962

(Cont. next page)

