

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 051040

PRIMARY CORNER DESCRIPTION W NW Cor. Venable DLC #51

Alias 052070 Description Int. SE Cor. Van Riper DLC #52  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1854

-----  
Set post, from which  
A B.Oak 8" dia. bears N.20°E., 58 lks.  
A W.Oak 10" dia. bears N.30°W., 67 lks.

Germond, For Stevens and Rehm - (about 1910) Volume 2  
Page 160 (and Pg. 285)

-----  
Set a Fir post, from which  
B.Oak 14" dia. bears S.57°W., 10 lks.  
R.Fir 18" dia. bears S.80°E., 39 lks.

Milo E. Godfrey, Dep. Co. Surv. - Vernon Tracy - Mike Stone  
July 20, 1962 - C.S. File 49/123-11

-----  
Found - Fir stump now 30", S.80°E., 25.7 ft. chopped open  
& found good scribing "C".  
B.Oak now 16", S.57°W., 6.6 ft., shows good scar.  
Didn't open.  
These 2 trees mkd. by Germond. No trace of either  
original BT.  
Set brass cap at cor. mkd: County Surveyor's Office, 1962  
T25S R6W W NW Cor. D.L.C. #51  
Blaze & rescribe 16" B.Oak S.57°W., 6.6 ft. mkd: "W NW  
DLC 51 CS BT".  
New BT - 6" D.Fir S.67°E., 8.3 ft. mkd: W NW DLC 51 CS BT.  
Fence cor. (fences E. & S.) bears S.45°E., 9.0 ft.

Fd. Ok - Oct. 1997 - D. Edwards - M 127-65

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J.  
Flause - 2/4/98 - C.S. File 64/79-20

-----  
Found - 2½" dia., brass cap on a 1½" O.D. iron pipe,  
protrudes 10" above ground.  
14" now 15" dia., B.Oak with a fully healed blaze,  
bears S.57°W., 6.6 ft. (Agrees with rec.)  
1910?  
18 now 28" dia., 2½" high rotted D.Fir stump no  
scribing visible, bears S.80°E., 25.7 ft.  
(Agrees with rec.) 1910?

(Cont. next page)

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 051040

PRIMARY CORNER DESCRIPTION W NW Cor Venable DLC #51

Alias 052070 Description Int SE Cor Van Riper DLC #52

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

6" now 12" dia., D.Fir with a fully healed double blaze, bears S.67°E., 7.2 ft. (Rec. S.67°E., 8.3 ft., dist. goes to center of trunk blaze high, tree has a pistol butt) 1962  
New BTs- 24" dia., Madrone, double blazed and scribed "INT SE DLC 52 CS BT", bears N.7°W., 14.0 ft.  
7" dia., D.Fir, double blazed and scribed "INT SE DLC 52 CS BT" bears S.18°W., 14.0 ft.