

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 051060

PRIMARY CORNER DESCRIPTION Int. "L" DLC R.M. Venable DLC 51

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854 -
(DCSO DLC records page 231)

Set post in prairie, deposited stone 7x6

Adam DeGroot - For: Waggoner - June 2018 - M171-44

No evidence of the original corner.
At the proportioned position:
Set - A 5/8"x30" iron rod, 27" in the ground, with a 2"
aluminum cap mkd:

BTS SURVEYING INC
T25S R6W
S16
 • INT EL
 | DLC
 | 51
 |
 2018
 PLS 89398

New BTs- A 18" Ash bears S.17°45'E., 41.5 ft. scribed "INT EL
CL 51 BT"
 A 14" D.Fir bears S.81°15'W., 56.6 ft. scribed "INT
EL CL 51 BT"

Corner falls 15 ft west of the N-S fenceline, and 15 ft south
from edge of Wetlands-Swale
All new BTs have double blazed faces with a 1" brass washer
stamped "DEGROOT PLS89398" nailed into the lower blaze.
Bearings are taken to the center of the tree at the root
crown and distances are measured to a mag-hub chaining nail
in the root crown at the side and center of the tree with a
total station. All BTs have a 6" red band painted around the
tree and the blazed face painted red and bearing tree signs
nailed to the tree.