

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 052020

PRIMARY CORNER DESCRIPTION NW Cor. Van Riper DLC #52

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Addison R. Flint, Contract #28 dated April, 1854

Set post, from which

- A W.Oak 15" dia. bears N.15°W., 152 lks.
- A B.Oak 18" dia. bears N.75°E., 102 lks.
- Fresh water spring N.82°E., 358 lks.

F.C. Frear, for H.J. & F.A. Cole - Field Book 44 Pg. 35
Oct. 28, 1919 -

Renewed from old BTs, both standing & in good condition.
I remarked same and set a 1½" x 40" Iron pipe for corner.

Milo E. Godfrey, Deputy Co. Surveyor - Mike Stone -
Oct. 1962 - C.S. File 49/123-29

Found - 1½" I. Rod set by Frear, 1919, almost flush with
top of ground.
34" W.Oak N.50°W., 15.2 ft. Tree had been cut open
previously & entire center of tree rotted away.
22" B.Oak S.14½°E., (Not S.12°E.) 64.7 ft. Portions
of Frear's scribing still visible on not com-
pletely grown over face.
Set brass cap at cor. alongside I.Rod mkd. County Surveyor's
office, 1962 T25S R6W N.W. DLC [.
New BTs - 10" D.Fir N.10°E., 24.7 ft. mkd. NW DLC 52 CS BT.
7" B.Oak S.67°E., 12.0 ft. mkd. NW DLC 52 CS BT.
A fence cor., fences running E. & S. bears N.40°E., 6.0 ft.

Found OK per M 101-70, Dec. 1989 - by Don Bentz