

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 057030

PRIMARY CORNER DESCRIPTION SW Cor. I. Smith DLC #57

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #28 dated April, 1854  
-----  
Set stone post 30 x 12 x 6, from which  
A W.Oak 12" dia. bears S.15°E., 18 lks.

Milo E. Godfrey, Deputy - V. Tracy and M. Stone  
April 11, 1963 - C.S. File 49/123-75  
-----

Found - Stone as called for in gov't notes (17"x5" top, 8"  
above ground) marks visible on stone "T25S R W"  
29" W.Oak S.30°E. (not S.15°E) 12 ft., shows very  
plain scar, did not chop open.  
New BT - 6" D.Fir S.69°W., 34.0 ft. mkd: S.W. DLC 57 CS BT.

Fd OK by K. DeGroot, May 1999 - M132-1

Douglas Co. Surveyors Office - John Pike - Pat Crawford -  
9/9/2004 - C.S. File 67/6-22  
-----

Found - Stone, approx. 5"x17" protrudes from ground 11".  
Faint marks visible on stone. Has indent near  
middle where I took measurements from. Stone is  
firmly set on nearly level ground.  
6" D.Fir now 23" dia., x 36" tall stump bears  
S.69½°W., 34.0 ft. (1963)  
29" W.Oak now 32" dia., x 15 " tall partially rotten  
stump bears S.33°E., 13.0 ft. (OBT)  
New - 7" dia., madrone double blazed & scribed SW DLC 57  
CS BT center of root crown bears N.34°E., 14.3  
ft.  
6" dia., madrone double blazed & scribed SW DLC 57  
CS BT center of root crown bears S.61½°E., 17.4  
ft.  
No other suitable trees in vicinity.  
Note - Stone lies on nearly level land in area that was  
logged over in past.  
Decl. 17½°E.