

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 058020

PRIMARY CORNER DESCRIPTION NW Cor. Knott DLC #58

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #28 dated April, 1854

Set stone post 15 x 8 x 3, from which
 An Ash 8" dia. bears N.15°W., 325 lks.
 An Ash 8" dia. bears N.35°E., 200 lks.

Ben B. Irving, Dep. Co. Surveyor - N.E. Richardson; James
McHugill - August 1938 - M 11-10 and C.S. File 37/198

Original stone in place, all bearing trees destroyed.
Drove an Iron Pipe 3/4" dia. alongside stone.
 An Ash 8" dia. bears N.50°E., 35 ft. blazed and scribed
 N.E. Cor. Cl. 58 C.S.B.T.

Milo E. Godfrey, Dep. Co. Surveyor - Wm. Stoffel; M Stone;
M. Darby - April-May 1964 - C.S. File 49/123-113

Found - 3/4" Pipe in line with fence running East.
 Ash stump N.50°E., 35.0 ft. good scribing found, BT.
New BTs - 12" Ash N.68°E., 45.1 ft. mkd. N.W. DLC 58 CS BT.
 10" Ash N.61½°E., 52.0 ft. mkd. N.W. DLC 58 CS BT.
Found - 3/4" Bolt w/square head 2.4 ft. south of 3/4" pipe.
 A telephone pole mkd. 32-55-16R 2 bears S.88°E.,
 23.8 ft.

Found July 1983, R. Dolan - M 94-50
Found and used by Carl Sweeden, May 1997 - M 127-5

Douglas County Surveyors Office - Randall Smith & Stephen
Flause - July 31, 1997 - C.S. 64/71-28

Mon. Fd.- 3/4" i.d. iron pipe protrudes 8" above ground in a
 N-S fence line.
 orig. stone not found or square head bolt noted in
 1964 renewal.

Bt's Fd.- No OBT's or BT from 1938 renewal found
 10" now 12" down Ash, with a unhealed blaze scribing
 visible "NW DLC 58 CS BT", position on root
 unknown down BT is near rec. "N.61½°E., 52'."
 12" now 13" dia. Ash, with a partially healed blaze,
 scribing visible "W DLC 58 S BT", bears
 N.64½°E., 46' (rec. N.68°E., 45.1').

(Cont. Next Page)

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 058020

PRIMARY CORNER DESCRIPTION NW Cor. Knott DLC #58

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

½" I.D. iron pipe protruding 8" above ground, bears North 12.5'.
Mon. Set- Corner lies under a fence line BC/IP not set
New Accessories -
5" Ash, double blazed and scribed "X BT", bears N.60°E., 32'.
4" Ash, double blazed and scribed "X BT", bears N.27°E., 17.3'.

Fd. OK by W. Rogers, Sept. 1999 - M132-17
Fd. OK by D. Edwards, Feb. 2001 - 2001-0079
Fd. ok by H. Pieske, Aug. 2004 - M145-24