

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 061010

PRIMARY CORNER DESCRIPTION WSW Cor. Gilbert DLC #61

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Addison R. Flint, Contract #28 dated April, 1854  
-----

Set post, from which  
    A B.Oak 8" dia. bears N.45°E., 20 lks.  
    Raised mound with trench as per instructions.

C.W. Springer, Deputy Co. Surveyor - For: Davison & Bemis  
February, 1923 - Volume 3 Page 138 and Field Book 60  
-----

Reset this cor. from tie given to sec. cor. Put in Iron  
Pipe 1½" x 30" and erected a mound of rock, from which  
    A B.Oak 6" dia. bears N.51°E., 129 lks. slope distance.

Milo E. Godfrey, Deputy Co. Surveyor; Vernon Tracy; Mike Stone  
November, 1962 - C.S. File 49/123-57  
-----

Found - 1 1/8" steel shaft in mound of rocks, set by  
          Springer in 1923.  
          15" B.Oak N.51°E., 85.1 ft. (slope dist.) Cut open  
          but entire center portion rotted away, no  
          scribing found, scars show plainly on surface.  
          Re-pile rocks around corner monument.  
New BTs - 6" D.Fir N.57½°E., 24.1 ft. mkd: WSW DLC 61 CS BT.  
          6" Pine S.2½°E., 31.0 ft. mkd: WSW DLC 61 CS BT.  
Old fence corner bears West 2.5 ft. Cor. lies on SE slope  
approx. 150 ft. North of stream.

Ken Hoffine - For: Lone Rock Timber Co. - March 2000 - M134-64  
-----

Found - 1¼" iron rod in a pile of stones.  
          20" D.Fir bears N.57½°E., 24.2 ft. (rec. N.57½°E.,  
          24.1 ft.) Well healed face & tag.  
          16" Pine bears S.3½°E., 31.1 ft. (rec. S.2½°E., 31.0  
          ft.) well healed face & tag.  
          23" D.Fir bears N.10½°W., 42.9 ft. We scribe WSW DLC  
          61 BT and tag tree.  
          20" D.Fir bears S.47°W., 72.4 ft. We scribe WSW DLC  
          61 BT & tag tree.  
Corner lies on East facing slope in a fence corner. Fence runs  
South & East.