

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 061020

PRIMARY CORNER DESCRIPTION Int. SW Cor. Gilbert DLC #61

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint - Contract #28 dated April, 1854

-----  
Set post, from which

A W.Oak 7" dia. bears N.5°W., 32 lks.

An Alder 8" dia. bears N.75°W., 18 lks.

-----  
C.W. Springer - Deputy Co. Surveyor - H.E. Bergh; W.A. Davidson; F.A. Bemis - For: Davidson & Bemis - Feb. 1923  
Volume 3 Page 182 (Field Book 60)

-----  
I look for evidence of the N.W. Interior L corner of the Joseph L. Gilbert Cl. #61. Failing to find any evidence, I compute a point at right angles to the section line common to secs. 1 & 2 & bearing S.89°16'E., 23.58 chs. I then drove

An Iron pipe 1½" x 30" at that point and from which:

A W.Oak 18" dia. bears N.50°W., 79.2 ft.

A W.Oak 6" dia. bears N.20°40'E., 25.4 ft.

said I.P. being the approx. location of the NW Int. L. Corner.

-----  
Don E. Garrett, For: Mrs. Paul Thinger, Sept. 1968  
Map File M 36-34

Found - 1½" Iron pipe, bent over.

Set - 5/8" Iron rod 4" in road bed, from which

26" W.Oak bears N.50°W., 79.2 ft. (I do not open)

10" W.Oak bears S.47°30'W., 31.1 ft. scribed Int.

L DLC 61 BT.

-----  
Found OK by K. Hoffine, March 2000 - M134-64