

PRIMARY CORNER DESCRIPTION Tsp. Cor. (SW Cor. Sec. 31)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Elder & Gile, Contract #31 dated April, 1853

Set post cor. to Tps. 25 and 26 S. and bet. Rgs. 6 and 7 W.
from which

An Ash, 14" dia. bears N.6°E., 829 lks. dist.

An Ash, 16" dia. bears N.2¼°W., 866 lks. dist.

Made trench, no other trees near.

Glenn Baughman, for: Bill Escalle - October 1974

Map File M 49-76

Set - Brass cap on a 1" I.P. on the inside edge of a dike
of a farm pond approx. 15 ft. from lower edge
of a steep bank between field & lower field
terrace.

BT - Only one tree close to corner which I scribed:
42" Oak bears N.61°W., 46.0 ft. scribed S36 BT.

Doug. Co. Surveyors Office - R.B. Kimberling - P.L. Earle
June 28, 1977 - C.S. 59/34-44

Found - Brass cap 6" above ground on a 1" I.P. stamped:

OLS 536

T 25 S

R				R	
6	S	36	S	31	5
W	S	1	S	6	W

1974

We stamped correction on BC to read: "OLS 536"

T 25 S

R				R	
76	S	36	S	31	56
W	S	1	S	6	W

T 26 S

1974

CS 1977

Found - A 42" Oak, now down, bears N.61°W., 46.0 ft. double
blazed & scribed "S 35 BT".

Set - Metal fence post with survey marker sign 1.0 ft.
North of BC.

Set a 5/8" I.R. 30" long 3" above ground with an
alum. cap stamped "B.O. 1" bears N.24°E., 74.0
ft.

(Cont. Next Page)

TOWNSHIP 25 RANGE 06 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION Tsp. Cor. (SW Cor. Section 31)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a metal fence post with survey marker sign 1.0 ft. West of Iron rod, point is on top of dike at west side of pond.
Set a 5/8" Iron rod 30" long 4" above ground with an alum. cap stamped "B.O. 2" bears S.4°W., 105.8 ft. Set a metal fence post with survey marker sign 1.0 ft. West of I.R. point is on edge of upper field.
7" Pear tree bears N.67°W., 107.3 ft. double blazed and marked "T25S R67 S36 CS BT".

Found OK by C. Sweeden, Aug. 2001 - M138-58

DCSO-GIS Corner visitation - 5/12/2004 - Typed: 1/24/2011 - C.S. File 67/33-1

Monument - 1.25 BC/IP
Comment - (needs) rehab

2